

## Recommended Change to Master Specification

Division 08800

### Glass Type Schedule - Fire Rated Glass

- GL-1      20-minute fire rated glass – doors only (1/4" thick)  
For use in 20-minute rated doors only. Basis of design is Superlite I 20 as manufactured by SAFTI *First*, (888) 653-3333 / fax (415) 822-5222 or approved equal.
- GL-2      45-minute fire rated glass (3/4" thick)  
For use in 45-minute door / sidelight / transom / window applications. Basis of design is SuperClear 45 HS or Superlite II-XL as manufactured by SAFTI *First*. (888) 653-3333 / fax (415) 822-5222 or approved equal.
- GL-3      60- or 90-minute fire rated **door** glazing 100 squares in. or less (3/4" thick)  
For use in 60- or 90-minute door applications, must comply with CPSC Category I and limited to 100 square inches in vision area. Basis of design is Superlite X-60 or X-90 as manufactured by SAFTI *First*. (888) 653-3333 / fax (415) 822-5222 or approved equal.
- GL-4      60- 90- or 120-minute fire rated glass  
For use in 60, 90, or 120 door / sidelight / transom / window / wall applications, must comply with ASTM E-119 requirements as a barrier to radiant heat. Basis of design is Superlite II-XL as manufactured by SAFTI *First*, (888) 653-3333 / fax (415) 822-5222 or approved equal. For use in GPX radiant heat barrier frames only.

Note: All applications subject to compliance with current building, safety and fire code requirements.

For more information please contact:

Ohio or Indiana – Adam Olson at (614) 507-0023 or [adam@oapinc.us](mailto:adam@oapinc.us).

Michigan – Tom Olson at (734) 777-6788 or [tom@oapinc.us](mailto:tom@oapinc.us)

W. PA or WV – Joe Marini at (412) 552-8087 or [joe@oapinc.us](mailto:joe@oapinc.us)