

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name: BODY P261 POLYESTER FILLING PRIMER****Article number: 524****1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites**Product category PC9b Fillers, putties, plasters, modelling clay****Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities****Environmental release category ERC2 Formulation into mixture****Article category AC1 Vehicles****Application of the substance / the mixture Surface protection****1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:****H.B. BODY S.A****B' ENTRANCE BLOCK 50 DA9 & MB6 Str****THESSALONIKI INDUSTRIAL AREA****57.022, SINDOS****THESSALONIKI,GREECE****Ph: +30 2310 790 000****Fax: +30 2310 790 033****www.hbbody.com****email: hbbody@hbbody.com****Further information obtainable from:****H.B. BODY S.A****B' ENTRANCE BLOCK 50 DA9 & MB6 Str****THESSALONIKI INDUSTRIAL AREA****57.022, SINDOS****THESSALONIKI,GREECE****Ph: +30 2310 790 000****Fax: +30 2310 790 033****www.hbbody.com****email: hbbody@hbbody.com****1.4 Emergency telephone number:****Regional Medicines and Poisons Information Centre NI****Pharmacy Department, Royal Hospital Suite****Grosvenor Road Belfast****Telephone: +44 28 90 63 2032****Fax: +44 28 90 24 80 30****Emergency telephone: 844 892 0111****E-mail address: nirdic.nirdic@belfasttrust.hscni.net**

Trade name: BODY P261 POLYESTER FILLING PRIMER

(Contd. of page 1)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02



GHS07



GHS08

Signal word Danger

Hazard-determining components of labelling:

styrene

titanium dioxide

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure. Route of exposure: Inhalation.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

Trade name: BODY P261 POLYESTER FILLING PRIMER

(Contd. of page 2)

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures****Description:** Mixture of hazardous substances**Dangerous components:**

CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 RTECS: WL 3675000 Reg.nr.: 01-2119457861-32-0011 01-2119457861-32-0009	styrene ⚠ Flam. Liq. 3, H226 ⚠ Carc. 2, H351; Repr. 2, H361d; STOT RE 1, H372 ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	30 - <35%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000 Reg.nr.: 01-2119471330-49-0001	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10 - <15%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide ⚠ Carc. 2, H351	5-<10%
CAS: 68409-81-4	FATTY ACIDS C6-C19 ⚠ Carc. 2, H351	0.1-<2.5%
CAS: 123-31-9 EINECS: 204-617-8 Index number: 604-005-00-4 RTECS: MX 3500000	1,4-dihydroxybenzene ⚠ Muta. 2, H341; Carc. 2, H351 ⚠ Eye Dam. 1, H318 ⚠ Aquatic Acute 1, H400 (M=10) ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	<0.1%

Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation: In case of unconsciousness place patient stably in side position for transportation.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.

After swallowing: If symptoms persist consult doctor.**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**For safety reasons unsuitable extinguishing agents:** Water with full jet**5.2 Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.**5.3 Advice for firefighters**

Firefighters should always use protective equipment and breathing apparatus when handling fire coming from these products

Special protective equipment and fire fighting procedures:

Mouth respiratory protective device.

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

(Contd. on page 4)

Trade name: **BODY P261 POLYESTER FILLING PRIMER**

(Contd. of page 3)

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

100-42-5 styrene

WEL Short-term value: 1080 mg/m³, 250 ppm

Long-term value: 430 mg/m³, 100 ppm

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m³, 500 ppm

123-31-9 1,4-dihydroxybenzene

WEL Long-term value: 0.5 mg/m³

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

(Contd. on page 5)

Trade name: BODY P261 POLYESTER FILLING PRIMER

(Contd. of page 4)

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.

For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Rubber gloves

Eye protection:

Tightly sealed goggles

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information****Appearance:**

Form:

Fluid

Colour:

According to product specification

Odour:

Characteristic

Odour threshold:

Not determined.

pH-value:

Not determined.

Change in condition

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

55 °C

Flash point:

< 0 °C

Flammability (solid, gaseous):

Not applicable.

(Contd. on page 6)

Trade name: BODY P261 POLYESTER FILLING PRIMER

(Contd. of page 5)

Autoignition temperature:	465 °C
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Risk of explosion by shock, friction, fire or other sources of ignition.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	13.0 Vol %
Vapour pressure at 20 °C:	233 hPa
Density at 20 °C:	1.4 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	45.6 %
VOC (EC)	530.0 g/l
Solids content (volume):	54.3 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity**10.1 Reactivity** No further relevant information available.**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.**10.3 Possibility of hazardous reactions** No dangerous reactions known.**10.4 Conditions to avoid** No further relevant information available.**10.5 Incompatible materials:** No further relevant information available.**10.6 Hazardous decomposition products:** No dangerous decomposition products known.**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h 127 mg/l (rat)

100-42-5 styrene

Oral LD50 5000 mg/kg (rat)

Inhalative LC50/4 h 24 mg/l (rat)

67-64-1 acetone

Oral LD50 5800 mg/kg (rat)

(Contd. on page 7)

Trade name: BODY P261 POLYESTER FILLING PRIMER

(Contd. of page 6)

Dermal	LD50	20000 mg/kg (rabbit)
13463-67-7 titanium dioxide		
Oral	LD50	>20000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)
64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)
123-31-9 1,4-dihydroxybenzene		
Oral	LD50	320 mg/kg (rat)

Primary irritant effect:**Skin corrosion/irritation**

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity**

Suspected of causing cancer.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure Based on available data, the classification criteria are not met.**STOT-repeated exposure**

Causes damage to organs through prolonged or repeated exposure. Route of exposure: Inhalation.

Aspiration hazard Based on available data, the classification criteria are not met.**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

12.2 Persistence and degradability

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

12.3 Bioaccumulative potential No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment**PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Trade name: BODY P261 POLYESTER FILLING PRIMER

(Contd. of page 7)

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information**14.1 UN-Number**

ADR, IMDG, IATA

UN1263

14.2 UN proper shipping name

ADR

UN1263 PAINT, special provision 640D

IMDG, IATA

PAINT

14.3 Transport hazard class(es)

ADR

Class
Label

3 (F1) Flammable liquids.

3

IMDG, IATA

Class
Label

3 Flammable liquids.

3

14.4 Packing group

ADR, IMDG, IATA

II

14.5 Environmental hazards:

Marine pollutant:

No

14.6 Special precautions for user

Warning: Flammable liquids.

Danger code (Kemler):

33

EMS Number:

F-E,S-E

Stowage Category

B

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

Transport category

2

Tunnel restriction code

D/E

IMDG

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

(Contd. on page 9)

Trade name: BODY P261 POLYESTER FILLING PRIMER

(Contd. of page 8)

UN "Model Regulation":

UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02

GHS07

GHS08

Signal word Danger**Hazard-determining components of labelling:**

styrene

titanium dioxide

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure. Route of exposure: Inhalation.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 28, 29

15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.**SECTION 16: Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

(Contd. on page 10)

Trade name: BODY P261 POLYESTER FILLING PRIMER

(Contd. of page 9)

- H341 Suspected of causing genetic defects.
 H351 Suspected of causing cancer.
 H361d Suspected of damaging the unborn child.
 H372 Causes damage to organs through prolonged or repeated exposure. Route of exposure: Inhalation.
 H400 Very toxic to aquatic life.

Contact:**H.B BODY S.A****Ms Olympia Stamkou****Ph: +30 2310 790 032****fax: +30 2310 790 033****email: stamkou@hbbody.com****Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 2: Germ cell mutagenicity – Category 2

Carc. 2: Carcinogenicity – Category 2

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

*** Data compared to the previous version altered.**

GB

(Contd. on page 11)

Trade name: BODY P261 POLYESTER FILLING PRIMER

(Contd. of page 10)

Annex: Exposure scenario

Short title of the exposure scenario

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC9b Fillers, putties, plasters, modelling clay

Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

Article category AC1 Vehicles

Environmental release category ERC2 Formulation into mixture

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.

Duration and frequency Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Fluid

Concentration of the substance in the mixture The substance is main component.

Other operational conditions

Other operational conditions affecting environmental exposure No special measures required.

Other operational conditions affecting worker exposure

Avoid contact with eyes.

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Other operational conditions affecting consumer exposure Keep out of the reach of children.

Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures

Worker protection

Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Ensure that suitable extractors are available on processing machines

Provide explosion-proof electrical equipment.

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

Pregnant women should strictly avoid inhalation or skin contact.

Tightly sealed goggles

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Keep locked up and out of the reach of children.

Provide instructions for use.

Observe consumer information and advice on safe use.

Ensure adequate labelling.

Environmental protection measures

Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Soil The product is only processed over the concrete collecting basin.

Disposal measures Ensure that waste is collected and contained.

(Contd. on page 12)

Trade name: BODY P261 POLYESTER FILLING PRIMER

(Contd. of page 11)

Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste type Partially emptied and uncleaned packaging

Exposure estimation

Consumer This product is to be used by professional technicians only.

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.