

3000XLS

Residential
Single / Dual

Swing Gate Operator



*For Swing Gates
UP TO 16 ft. long and
650 lbs. per leaf*



All Models Listed
UL 325 Compliant



Intertek

Supporters and Proud Members of



QUICK INSTALL *with Dual Sense Technology*

- No electrician or welder required
- No photo beams required
- UL 325 compliant, latest revision
- Solar Compatible

Linear PRO ACCESS

ELECTRICAL

- 12 Volt DC / 7.0 amp hour, sealed, rechargeable battery (included). Battery charge is maintained by a 120V AC/60 Hz input, 18V AC, 40 VA. output, transformer regulated to 14V DC through control board
- Powered by a reliable 12 Volt (120 Watt) DC motor, 16:1 planetary gear drive system
- “Sleep draw” is 15 mA; “active draw” is 3 to 7 amps

MECHANICAL

- The control board can be programmed for pull-to-open or push-to-open
- Operating temp -5 F (-21C) to +160 F (71 C)
- Opening time: from 15 to 18 seconds
- Range of arm stroke: up to 16" (41 cm)
- Operator length: mounting point to mounting point with arm fully retracted, 40.25" (102 cm)
- Operation, diagnostic and safety alarms
- Inherent obstruction sensing
- Soft start/soft stop for long mechanical life expectancy
- Auto close adjustable 3–120 second delay

CAUTIONS



- Automatic gates not for pedestrians
- Automatic gate operators designed for vehicular traffic only; operators are powerful and can cause serious injury or death; DIRECT ALL PEDESTRIAN TRAFFIC TO SEPARATE PEDESTRIAN GATE

MODEL	TYPE	VOLTS	Max. Gate Length	Max Gate Weight	Gate Speed
PRO-SW3000 XLS	Single	12 V DC	16'	650 lbs.	15-18 sec.
PRO-SW3200 XLS	Second Arm				

(solar charger optional)

DUAL GATES

- The PRO-SW3200XLS works as a second gate operator when combined with a PRO-SW3000XLS. The PRO-SW3200XLS includes a 40ft power cable.



FEATURES:

- Increased operating speed by 10%
- NEW rev-counter board with reed switch technology
- IMPROVED front mount and scraper seal design
- True soft start/soft stop operation
- One button auto-memorization of digital transmitter code
- Includes battery backup, 318 MHz RF radio receiver, entry transmitter, AC transformer and all necessary mounting hardware for post-mounted installation
- Solar Compatible
- Low voltage system — no electrician or welding required
- 2-year warranty (residential applications only)
- Extended Life — Enhanced motor design makes this opener ideal for today's single-family homes or ranches
- Works on all types of gates: chain link, tube, panel, ornamental, wood and vinyl
- Full systems capable, control board includes adjustable obstruction-sensing, gate sequencing and auto close settings
- UL rated for Class I. System certified to be in compliance with UL 325, latest revision

Linear
PRO ACCESS®

800-543-4283 • linearproaccess.com