

## FULL SYNTHETIC MULTI- VEHICLE ATF

### DESCRIPTION:

**TECHSELECT® Full Synthetic Multi-Vehicle ATF** represents the latest technology in full synthetic automatic transmission fluids. It is specifically formulated for the newest generation of high efficiency transmissions and is also a fuel efficient choice for older models as well.

**TECHSELECT® Full Synthetic Multi-Vehicle ATF** meets the requirements of JASO M3150-2013 1A-LV specification. Also suitable for use in many applications including General Motors, Ford, FCA/Chrysler, Toyota/Lexus/ Scion (T-III, IV, WS), Nissan/Infiniti (Matic D, J, K, S, W), and Honda/Acura (ATF Z-1, DW-1) transmissions as well as some transmissions installed in Hyundai/ Kia (SP-II, III, IV, Red-1K), Isuzu (SCS, ATFII, III), Jaguar, Land Rover, Mazda (F-1, FZ, M-III, T-IV, MV), Mercedes-Benz (236.10, 236.3, 236.5, 236.6, 236.7, 236.9, 236.15), Mitsubishi (Diamond SP, II, III, ATF J2, J3), Porsche, BMW (LA2634, LT71141), MINI, SAAB, Subaru (HP), Suzuki, Volvo and VW/Audi (09A, 09G) cars and light trucks. It is also suitable for transfer case applications calling for Ford XL-12 fluid.

This product is NOT recommended for Ford Type F, MERCON® ULV, DEXRON® HP, Continuously Variable Transmissions (CVT) or Double Clutch Transmissions (DCT) which require specialized OEM fluids. Check owner's manual for specific recommendations.

### PERFORMANCE BENEFITS:

- Improved oxidation and thermal stability
- Full synthetic formula
- Outstanding low temperature performance
- Superior anti-wear protection
- Improved torque transfer

Note: This product is not for sale or use in the State of California.

### TYPICAL PROPERTIES\*:

API Gravity	34.8
Sp. Gr. @ 60 ° F	0.8468
Flash. COC. ° F	400
Pour Pt.. ° F	-55
Viscosity. cP @ -40 ° C	12100
Viscosity, cSt @ 40 ° C	32
cSt @ 100 ° C	6.3
Viscosity Index	152
Color	Red

\* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.



This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.



Revised 10/2020 page 1  
TSFSATF

## FULL SYNTHETIC MULTI- VEHICLE ATF

**TechSelect Full Synthetic Multi-Vehicle Automatic Transmission Fluid is suitable for use in the following applications:**

OEM / ATF	APPLICATION	OEM / ATF	APPLICATION
Allison	C4 & TES-389		P/N XT-10-QLVC
ATF	Esso LT 71141	Ford / Lincoln / Mercury	P/N XT-2-QDX [M]
	Shell 3353 & 134		P/N XT-2-QSM [Syn]
	JWS 3309		P/N XT-5-QM or -DM [V]
	Mobil ATF 3309		P/N XT-6-QSP or -DSP [SP]
	Shell 3403-M115 & M-1375.4		P/N XT-8-QAW [Premium]
	Shell LA 2634 & L12108		P/N XT-9-QMM5 [FNR5]
	Texaco ETL 7045E		WSS-M2C922-A1
	Texaco ETL 8072B		AW1
	Texaco N402		II/IIID/IIIE/IIIG/IIIH
	ZF Lifeguard Fluid 6/8		VI
Bentley	P/N PY112995PA		P/N 12378515 [Synthetic]
BMW / MINI	P/N 81 22 9 400 272/275	GM / GMC / Opel / Saturn	P/N 19 40 700
	P/N 81 22 9 407 858/859		P/N 19 40 767
	P/N 83 22 0 024 359		P/N 21005966 Transaxle
	P/N 83 22 0 026 922		P/N 22717466
	P/N 83 22 0 142 516		P/N 88863400
	P/N 83 22 0 397 114		P/N 88863401
	P/N 83 22 0 402 413		P/N 88900925
	P/N 83 22 0 403 248		P/N 9986195
	P/N 83 22 0 403 249		T-IV
	P/N 83 22 7 542 290		Type A Suffix A
	P/N 83 22 9 407 765		
	P/N 83 22 9 407 807		Honda / Acura
	P/N 8322 2152426		DW-1 & Z-1
	P/N 83 22 2 289 720		ATF-Type 3.1
	Chrysler / Dodge / Jeep		+3, +4
AS68RC, AS69RC, ASRC		Genuine ATF	
MB236.12		JWS-3309 T-4	
P/N 05127382AA		NWS-9638 T-5	
P/N 68043742AA		P/N 040000C90SG	
SP-III		P/N UM040 CH20 Red-1	
P/N 68171866AA (ATF SP4)		SP-II/III/IV/M	
P/N 68157995AA (ZF 8-speed)		SPH-IV & SP-IV RR	
P/N 68157995AB (ZF 9-speed)			
P/N 68218925AA (F 8 & 9 speed)		Idemitsu	
Fiat/ Mercedes / Daimler	AW-1	Isuzu	ATF HP
	MB 236.3/5/6/7/8/9		K17
	MB 236.10/11/91		ATF II/III
	MB 236.12/14/15/41		Genuine ATF
			P/N 08200-9001
			SCS

## FULL SYNTHETIC MULTI- VEHICLE ATF

**TechSelect Full Synthetic Multi-Vehicle Automatic Transmission Fluid is suitable for use in the following applications:**

OEM / ATF	APPLICATION	OEM / ATF	APPLICATION
Jaguar	Fluid 8432	PSA Peugeot Citroën	P/N Z 000169756
	JLM 20238	Renault	Matic D2
	JLM 20292	Saab	3309 - T-IV
	JLM 21044	SSANG YONG	P/N 93 165 147 - AW-1
	K17	Subaru	HP
	WSS-M2C922-A1		P/N K0140Y0700
	02JDE 26444	Suzuki	3314/3317
JASO	M315, Class 1A	Toyota / Lexus / Scion	Type D-III/T-T-III/T-IV Type WS
Land Rover	P/N TYK500050 P/N LR023288	Volkswagen / Audi	G 052 025 A2
MAN	339A		G 052 055
Maserati	P/N 231603		G 052 162 (-A1, -A2)
Mazda	F-1 & FZ		G 052 533
	JWS3317		G 052 990 (A2)
	M-5, P/N XT-9-QMM5; M-V, MES MN 117C		G 055 005 (-A, A2)
	M-III		G 055 025 (A2)
	Type T-IV		G 055 540 (A2) (A1) (A6)
Mitsubishi	ATF-J2		G US 000 162
	ATF-J3		G 055162 (A2) (A6)
	SP, P/N MS991156	G 060162 (A2) (A1) (A6)	
	SP-II/III	P/N 1161521	
Nissan / Infinity	402	Volvo	P/N 1161540 / 1161640 AW-1, P/N 31 256 774 or 31 256 775
	Matic-D/J/K/W	Volvo Constr. Equip. (VCE)	1273,41
	Matic-S	ZF	TE-ML 11A/11B
Porsche	P/N 000 043 204 41		Lifeguardfluid 6/6 Plus
	P/N 000 043 205 09		Lifeguardfluid 8
	P/N 000 043 205 28		
	P/N 000 043 304 00		
	P/N 999 917 547 00 (A2)		