

Copper Deactivator, UV Tracer

A silica thickened, medium viscosity, synthetic hydrocarbon grease for lubrication and protection of electrical contacts. Benefits include good water resistance.

Ford: WSB-M1C239-A, GM: 9986087, DaimlerChrysler: MS-9469

Lubricant Properties		Typical value	Test Method	
Recommended Service Range (°C)		-40 to 135		
Thickener		Silica		
Base oil	Type	Polyalphaolefin		
	Kinematic viscosity	100°C 40°C -30°C	39.4 cSt 400 cSt 213788.5 cSt	
	Viscosity Index	147.5	ASTM D-2270	
	Flash point	°C	321 ASTM D-92	
	Pouring point	°C	-36 ASTM D-97	
Typical Properties of the Grease		Typical value	Test Method	
Color, Appearance		Water White, Smooth		
Penetration (1/10 mm)	Unworked	266	ASTM D-217	
	Worked	60X		286
		10K		303
		100K		311
	NLGI Grade	2		
Density	25°C	0.88	NYE CTM	
Oil Separation	24 hour(s)	100°C	1.5 % ASTM D-6184	
Evaporation	24 hour(s)	100°C	0.3 NYE CTM	

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1510)

Distributed by Newgate Simms Limited

Broughton Mills Road, Bretton, Chester, CH4 0BY, United Kingdom
+44(0)1244 660771 www.newgatesimms.com info@newgatesimms.com