

## EP Fortified, Rust Inhibited

A lithium soap thickened, blended base oil gear grease suited for long life metal gears in automotive starters, power tools, and heavily loaded mechanical applications.

Lubricant Properties		Typical value	Test Method
<b>Recommended Service Range (°C)</b>		-50 to 130	
<b>Thickener</b>		Lithium Soap	
<b>Base oil</b>	Type	PAO/Ester	
	Kinematic viscosity	100°C	6.228 cSt
		40°C	33.593 cSt
		-40°C	14410 cSt
	Viscosity Index		136.7
	Flash point	°C	252
	Pouring point	°C	-52
			ASTM D-445
			ASTM D-2270
			ASTM D-92
			ASTM D-97
Typical Properties of the Grease		Typical value	Test Method
<b>Color, Appearance</b>		Black, Smooth	
<b>Penetration (1/10 mm)</b>	Worked	60X	275
	Worked	10K	292
	Unworked		261
	NLGI Grade		2
<b>Density</b>		25°C	0.91 g/cm <sup>3</sup>
<b>Oil Separation</b>	24 hour(s)	100°C	4.5 %
<b>Evaporation</b>	24 hour(s)	100°C	0.22 %
		150°C	2.76 %

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1511)

**Distributed by Newgate Simms Limited**

Broughton Mills Road, Bretton, Chester, CH4 0BY, United Kingdom  
+44(0)1244 660771      www.newgatesimms.com      info@newgatesimms.com