

- Over 20 models to fit any application
- All parts in stock
- All pumps include "Overload Protection"
- Release valve is made of one piece, rigid copper construction
- Reinforced handles with ergonomic design
- Hand and foot release for extra safety and efficiency
- 2 year warranty on pump
- 1 year warranty on fork frame
- 90 day warranty on wheels, axles, and bearings
- Special application wheels available



Available Models For Manual Pallet Jack

Model No.	Type	Capacity (lbs)	Fork Size	Distance Between Forks	Fork Clearance	Fork Width	Min. HT/Max. HT	Wheels	Unit WT (lbs)
ML55-2	Standard	5500	27" X 48"	14.37"	1.18"	6.3"	2.9"/7.6"	Polyurethane	160
ML55L	Easy Moving	5500	27" X 48"	14.37"	1.18"	6.3"	2.9"/7.6"	Super Polyurethane	160
ML55N	Nylon wheel	5500	27" X 48"	14.37"	1.18"	6.3"	2.9"/7.6"	Nylon	160
ML66	High capacity	6600	27" X 48"	14.37"	1.18"	6.3"	2.9"/7.6"	Polyurethane	170
ML77	High capacity	7700	27" X 48"	14.37"	1.18"	6.3"	2.9"/7.6"	Polyurethane	220
ML110	High capacity	11000	27" X 48"	14.37"	0.55"	6.3"	3.0"/7.6"	Polyurethane	227
ML1636	Narrow/Short	2200	16" X 36"	4.17"	0.87"	5.9"	2.9"/7.6"	Polyurethane	130
ML1648	Narrow	2200	16" X 48"	4.17"	0.87"	5.9"	2.9"/7.6"	Polyurethane	140
ML2036	Narrow/Short	5500	20.5" X 36"	7.87"	1.18"	6.3"	2.9"/7.6"	Polyurethane	145
ML2042	Narrow/Short	5500	20.5" X 42"	7.87"	1.18"	6.3"	2.9"/7.6"	Polyurethane	150
ML2048	Narrow	5500	20.5" X 48"	7.87"	1.18"	6.3"	2.9"/7.6"	Polyurethane	155
ML2736	Short	5500	27" X 36"	14.37"	1.18"	6.3"	2.9"/7.6"	Polyurethane	150
ML2742	Short	5500	27" X 42"	14.37"	1.18"	6.3"	2.9"/7.6"	Polyurethane	155
ML2760	Long	4400	27" X 60"	14.37"	1.18"	6.3"	2.9"/7.6"	Polyurethane	190
ML2772	Long	3300	27" X 72"	14.37"	1.18"	6.3"	2.9"/7.6"	Polyurethane	220
ML2796-44	Super Long	4400	27" X 96"	14.37"	0.78"	6.3"	2.9"/7.6"	Polyurethane	300
ML2048L	Low profile/Narrow	3300	20.5" X 48"	8.66"	0.55"	5.9"	2.0"/5.5"	Polyurethane/steel	165
ML2748L	Low profile	3300	27" X 48"	14.37"	0.55"	5.9"	2.0"/5.5"	Polyurethane/steel	170
ML3348ULP	4-way/Ultra low profile	2200	33" X 48"	23.5"	0.55"	4.75"	1.9"/6.5"	Polyurethane/steel	220
ML3348LP	4-way/low profile	3300	33" X 48"	20.5"	0.55"	5.9"	2.0"/6.5"	Polyurethane	220
ML55SS	Stainless Steel	5500	27" X 48"	14.37"	1.18"	6.3"	2.9"/7.6"	Nylon	165
ML55GLV	Galvanized	5500	27" X 48"	14.37"	1.18"	6.3"	2.9"/7.6"	Nylon	165
ML55HB	Hand break	5500	27" X 48"	14.37"	1.18"	6.3"	2.9"/7.6"	Polyurethane	180
SPT50	Scale	4400	27" X 48"	14.37"	0.7"	6.7"	2.9"/7.51"	Polyurethane	290
HL33	High lift	2200	27" X 45"	14.37"	N/A	6.3"	3.5"/31.5"	Polyurethane	295
HL2045	High lift/Narrow	2200	20.5" X 45"	7.87"	N/A	6.3"	3.5"/31.5"	Polyurethane	240