

TegraGuard Colour Coat

System	TegraGuard Anti Graffiti System
Product Code	WB201AG
Product Description	A water based, low odour, single pack system formulated to provide an intermediate layer to increase opacity and substrate hiding power for the TegraGuard Titanium AG system.
Key System Benefits	The TegraGuard Titanium AG Finish is a unique coating system that can withstand repeated heavy duty cleaning cycles without a loss of performance. Due to its ultra high solids formulation it has exceptional hiding power often allowing a one coat finish on cyclical maintenance.
Main Uses	The TegraGuard Titanium AG System has been designed to protect masonry and metal substrates where heavy duty performance combined with a long service life is required.
Pack Size	5 litres
Coverage Rate	14m ² /litre on smooth non porous surfaces.
Colour Range	BS4800, NCS, RAL and colour matching service on request
Application	Brush or short/medium pile roller. Do not apply or allow to dry at temperatures below 3°C or if condensation is likely to occur.
Mix Ratio	Single pack as supplied
Pot life	N/A
Drying Time	2 hours at 20°C <i>Note: Drying times will be shortened by higher and lengthened by lower temperatures</i>
Over Coating Interval	Minimum: 24 hours, Maximum: 21 days
Flash Point	Above 32°C
Storage	Store at temperatures between 5°C and 25°C. Protect from frost.
Shelf life	6 months in original unopened containers
Health & Safety	Refer to current copy of Health and Safety Data Sheet
Disclaimer:	<i>The information given above is true and accurate to the best of our knowledge and is given in good faith but without any warranty. Please ensure you are reading a current and updated copy of this data sheet Integra Coatings Limited will not accept any claim for consequential or incidental damages.</i>