

**TegraGuard Satin AG Finish**

<b>System</b>	<b>TegraGuard Satin Anti-Graffiti System</b>
<b>Product Code</b>	<b>WB331SN</b>
<b>Product Description</b>	A chemically resistant, twin pack resin system specially formulated to provide an exceptionally hard wearing surface with an easy clean graffiti resistant finish.
<b>Key System Benefits</b>	The TegraGuard Satin AG System provides a tough, durable and non-sacrificial finish that enables graffiti to be removed quickly and effectively. TegraGuard Satin AG Finish can withstand repeated cleaning cycles without a loss of performance.
<b>Main Uses</b>	The TegraGuard Satin AG System has been designed to protect masonry and metal substrates where heavy duty performance combined with a long service life is required.
<b>Pack Size</b>	5 litres
<b>Coverage Rates</b>	15 m <sup>2</sup> /litre on smooth non porous surfaces
<b>Colour Range</b>	BS4800, RAL, NCS and colour matching on request.
<b>Application</b>	Brush or short/medium pile roller. Do not apply or allow to dry at temperatures below 5°C or if condensation is likely to occur.
<b>Mix Ratio</b>	Twin-pack finish as supplied
<b>Pot life</b>	4 hours at 20°C
<b>Drying Time</b>	2 hours @ 20°C <i>Note: Drying times will be shortened by higher and lengthened by lower temperatures</i>
<b>Over Coating Interval</b>	Minimum: 24 hours, Maximum: 21 days
<b>Flash Point</b>	Non Flammable
<b>Storage</b>	Store at temperatures between 5°C and 25°C. Protect from frost.
<b>Shelf life</b>	12 months in original unopened containers
<b>Health &amp; Safety</b>	Refer to current copy of Health and Safety Data Sheet
<b>Disclaimer</b>	<i>The information given above is true and accurate to the best of our knowledge and is given in good faith but without any warranty. Please ensure you are reading a current and updated copy of this data sheet Integra Coatings Limited will not accept any claim for consequential or incidental damages.</i>