

## ALUMINUM HAZARDOUS LOCATION CLASS 1 DIV 2 Fixture

IR3-4-2-26-UNV-T8

IR3-4-2-46-UNV-T5HO

4-FT., 2-LAMP, T8 (32-watt), FLUORESCENT HAZARDOUS LOCATION FIXTURE

4-FT., 2-LAMP, T5HO (54 watt), FLUORESCENT HAZARDOUS LOCATION FIXTURE



### FIXTURE FEATURES

#### Intended Use

Intended for hazardous location applications:

- Class I, Div. 2-Groups A, B, C, D

Typical applications include solvent and cleaning areas, petrochemical facilities, marine facilities, waste treatment plants and food processing applications.

#### Construction

- Extruded aluminum housing and clear lens.
- End mounting brackets are standard with fixture.

#### Ballast

Energy efficient, 120-277 multi-volt, electronic, automatic resetting, program start (T5HO) and instant start (T8) ballasts are standard in all fixtures.

#### Listings

UL 595 – Outdoor Marine Type (salt water)

UL 844 – Class I, Div 2, A,B,C,D

Meets Coast Guard Specifications

#### Approximate Fixture Dimensions & Weights

Length: 49.75-inches

Width: 6.5-inches

Height (to top of fixture) 6.5-inches

Height (to top of mounting brackets) 11.5-inches

Weight: 33 lbs

#### Mounting

Fixture can be surface mounted or suspended.

#### Warranty

Fixture is warranted for five years from delivery date against manufacturing defects. Ballast warranty is provided through the ballast manufacturer.

#### Accessories

- Wire Guard
- Safety Cable
- Shock Mount

**ALUMINUM HAZARDOUS LOCATION CLASS 1 DIV 2 Fixture**  
IR3-4-2-26-UNV-T8  
IR3-4-2-46-UNV-T5HO

4-FT., 2-LAMP, T8 (32-watt), FLUORESCENT HAZARDOUS LOCATION FIXTURE  
4-FT., 2-LAMP, T5HO (54 watt), FLUORESCENT HAZARDOUS LOCATION FIXTURE



**DIMENSIONS**

- A- 49 <sup>3</sup>/<sub>4</sub> "
- B- 47 "
- C- 4 <sup>3</sup>/<sub>4</sub> "
- D- 7 "
- E- 6.5 "
- F- 6.5 "

