



# HPiX Series Inverters



## Standard Features

### User Friendly Interface

- LCD with Status, Meter and Alarm screens.
- Industrial style LED Mimic Diagram.
- Nine button control keypad.
- 200 event Alarm History with date and time stamp.
- Four remote alarm contacts (user configurable).
- RS-485, 2-wire interface with Modbus protocol.
- RS-232 interface with Philtex protocol.

### Power Circuit

- High frequency PWM switching technology, using IGBT's.
- Pure Sine Wave AC output.
- Low audible noise.
- High efficiency.
- Inverter Output isolation transformer provides galvanic isolation between DC and AC circuits.
- Powers virtually any load, compatible with Nonlinear and Active Power Factor Corrected AC Loads.
- Input and Output Circuit Breakers.
- Automatic DC Input Pre-charge circuit.

### Integral Static Bypass Switch

- Output power fully rated.
- Zero Break with 2 mSec detection time.
- User configured to operate in the Online ( Inverter preferred ) or the Offline ( AC line preferred ) mode.
- Provides maximum protection when operated in the Online Mode.
- Provides economy operation when operated in the Offline Mode.

### Packaging

- 23" Rack mount design. Rack sold separately.
- 2 to 5 KVA Inverter occupies 14" or 8 RU, 10 KVA Inverter occupies 19.25" or 11 RU
- Air intake at front and exhaust at rear. Top, bottom and side clearances are not required.
- Temperature controlled variable speed cooling fans.

**Model Number:**

# **HPiX 10K - 120 - N + OPTIONS**

Output  
Power

**2K:** 2 kVA  
**3K:** 3 kVA  
**5K:** 5 kVA  
**10K:** 10 kVA

Nominal DC  
Input Voltage

**24:** 24 Vdc  
**48:** 48 Vdc  
**120:** 120 Vdc  
**240:** 240 Vdc

AC Output  
Voltage (1 $\Phi$ )

**N:** 120V, 60Hz  
**A:** 220V, 50Hz  
**AS:** 230V, 50Hz  
**B:** 120/240V, 60Hz  
**C:** 240V, 60Hz  
**D:** 208V, 60Hz  
**E:** 277V, 60Hz  
**Y:** 220V, 60Hz  
**YS:** 230V, 60Hz

Options

**MBSXR:** External Rack mount  
Maintenance Bypass Switch.

**AL8:** Four contacts added for a  
total of eight Remote Alarm  
Contacts.

**SVW:** Replaces the RS-232 port  
with an internal Status-Via-Web  
Ethernet device.

**RACK:** 23" relay rack (84" tall).

**NS:** No Static Bypass Switch  
(Inverter Only).

Example: HPiX 5K-120-N+MBSX+AL8+SVW

Not all combinations are available, please see specific brochures or contact Philtek.

For other configurations and options, please contact Philtek.

For More Information please Contact:

In Canada

In USA

**Philtek Electronics Ltd.**

**Philtek Power Corp.**

Tel: (604) 270-4642

Tel: (360) 332-7252

Fax: (604) 270-8343

E-mail: [info@philtek.com](mailto:info@philtek.com)