

PURUS® AKELA™ NATURAL GAS ENGINE OIL DXE LOW ASH

Manufactured with highly refined base oils

DESCRIPTION: PURUS® AKELA™ DXE Low Ash Gas Engine Oils are high performance natural gas low ash engine lubricant formulations with a balanced and field-proven additive system. Formulated to provide excellent deposit, sludge and wear protection during high stress service. Excellent high temperature piston deposit performance maintains an engine's peak performance and preserves ring face and liner honing. Purposely selected supplementary antioxidants mitigate the impact of high temperature blow-by gases on viscosity and extend oil life. The advanced detergent system provides excellent valve, seat and guide protection while it minimizes catalyst plugging. The PURUS® AKELA™ DXE Low Ash Gas Engine Oils TBN retention combats oil degradation and provides protection in a high temperature acidic environment.

PURUS® AKELA™ DXE Low Ash Gas Engine Oils are formulated with low sulfur Group II base oils combined with a robust additive system containing ashless dispersant, oxidation and corrosion inhibitors, antifoam and anti-wear agents. These oils meet the performance requirements of major engine manufacturers such as *Caterpillar, Deutz-MWM, Guascor, Jenbacher, Wartsila, Waukesha and other turbocharged and naturally aspirated four stroke engines requiring low ash oils. PURUS® AKELA™ DXE Low Ash Gas Engine Oils meets API CD/CF performance in stationary gas engines. Recommended for Dresser Rand Categories I, II and III applications.

PURUS® AKELA™ DXE Low Ash Gas Engine Oils are a robust Low Ash Gas Engine oil formulation which meets Caterpillar's G3500 and G3600 series engine performance field test protocol.

PERFORMANCE BENEFITS:

- Maximize Engine Run Time
- Outstanding Engine Cleanliness
- Excellent Valve Recession Performance
- Excellent Piston Deposits Performance
- Outstanding TBN Retention and Resistance to Oil Degradation
- Extended Oil Drain Interval
- Improved Low Temperature Performance
- Catalyst Systems Compatible

*The values shown here are typical of current production. All of them may vary within modest ranges. Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.



This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

Revised 10/2019
PGDXELA page 1

PURUS[®] AKELA[™] NATURAL GAS ENGINE OIL DXE LOW ASH

Manufactured with highly refined base oils

TYPICAL PROPERTIES*:

SAE Viscosity	30	40	40CC	15W-40
Viscosity				
@40 °C, cSt	100	125	128	127
@100 °C, cSt	11.5	13.3	13.6	15.8
Viscosity Index	101	100	102	132
API Gravity	29	29	30	31
Flash, COC, °F	495	500	500	450
Pour Pt., °F (°C)	-22(-30)	-17(-27)	-32(-36)	-38(-39)
Sulfated Ash	0.47	0.47	0.47	0.47
TBN, ASTM D 2896	5.8	5.8	5.8	5.8
Zinc, ppm	270	270	270	270
Phosphorus, ppm	250	250	250	250