

PURUS® SYNTHETIC SAE 5W-30 AND 5W-40 API CK-4 ENGINE OILS

Manufactured with highly refined base oils and industry leading additive chemistry

DESCRIPTION: PURUS® Synthetic SAE 5W-30 and SAE 5W-40 API CK-4 Engine Oils are fully formulated for use in high-speed four-stroke cycle premium diesel engines designed to meet 2017 model year on-highway and Tier 4 non-road exhaust emission standards as well as for previous model year diesel engines. These oils are formulated for use in all applications with diesel fuels ranging in sulfur content up to 500 ppm. PURUS® Synthetic SAE 5W-30 and SAE 5W-40 API CK-4 Diesel Engine Oils are designed to provide enhanced protection against oil oxidation, viscosity loss due to shear, and oil aeration as well as protection against catalyst poisoning, particulate filter blocking, engine wear, piston deposits, degradation of low- and high-temperature properties, and soot-related viscosity increase.

APPLICATION: PURUS® Synthetic SAE 5W-30 and SAE 5W-40 API CK-4 Diesel Engine Oils

- API CK-4, CJ-4, CI-4 PLUS, CH-4
- API SN (SAE 5W-40)
- Cummins® CES 20086 and CES 20081 (SAE 5W-30) OEM Approval
- Mack® EOS-4.5, EO-0 Premium Plus, EO-N OEM Approval
- Mercedes Benz 228.31 OEM Approval
- Volvo® VDS-4.5, VDS-4 and VDS-3 OEM Approval
- Detroit™ DFS 93K222 and DFS 93K218 OEM Approval
- Renault® RLD-4, RLD- 3 OEM Approval
- Ford® WSS-M2C171-F1 OEM Approval
- MTU Category 2.1
- PACCAR MX-11, MX-13 PX-7, PX-9 (SAE 5W-30 and 5W-40)
- PACCAR PX-7, PX-9 (SAE 5W-40)
- Deutz DQC-111(SAE 5W-40)
- Caterpillar® ECF-3, ECF-2
- MAN M3575
- ACEA E9-16, E7-16

PERFORMANCE BENEFITS: PURUS® Synthetic SAE 5W-30 and SAE 5W-40 API CK-4 Diesel Engine Oils provide enhanced fuel economy which make them ideal for mixed fleet operations. They offer excellent low temperature properties which help with cold starts, outstanding oxidation stability and protect emission control systems.

PURUS[®] SYNTHETIC SAE 5W-30 AND SAE 5W-40 API CK-4 ENGINE OIL

Manufactured with highly refined virgin base oils and licensed additive systems

TYPICAL PROPERTIES*:

		SAE 5W-30	SAE 5W-40
Viscosity			
@ 40° C, cST	D445	69.9	88.7
@ 100° C, cST	D445	11.6	14.4
Viscosity Index	D2270	161	169
Pour Point °C (°F)	D97	-42(-44)	-40 (-40)
Flash Point °C (°F)	D92	218 (424)	238 (460)
TBN	D2896	11	11
Sulfated Ash, wt.%	D874	1.0	1
Cold Crank Simulator, cP	D5293	6330/-30°C	6240/-30°C
Mini-Rotary Viscometer TP1, cP	D4684	21600/-35°C	31300/-35°C



*Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all of our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either AIOD or its affiliates for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult your local AIOD Distributor if you require any further information.

Revised 09/2020

PHDSYN5W40CK page 2