

2007-2015 HARRIS SET UP SHEET:



AIR PRESSURES:

LF: 10 / RF: 15 / LR: 10 / RR: 14

STAGGER: 0-1" FRONT | 1-2" REAR

FRONTEND SETTINGS:

CASTER: LF +1.5 | RF +3.5 CAMBER: LF +4 | RF -6 TOE OUT: 1/2"

4-LINK ROD LENGTHS & POSITIONS:

LT: 16" C-C SHORT 7TH UP | RT: 16" C-C 5TH UP
LB: 14" C-C 5TH UP | RB: 14" C-C SHORT 5TH UP

J-BAR: START @ 19.5" 6" UP ON FRAME | CENTER OF PINION

2-LINK ROD LENGTHS & POSITIONS

LEFT: 16" C-C 9th UP | RIGHT: 16" C-C 6th UP

PANHARD BAR: START @ 23.5" 14 DEGREES | 3" BELOW CENTER OF AXLE

PULL BAR: START @ 34" | 7 - 8.5 DEGREES PINION ANGLE

2ND HOLE UP ON HOUSING | 2ND HOLE UP ON FRAME

SPRINGS:

LF: 550# | RF: 600# | LR: 13"/16" 200# | RR: 11"/13" 200#

RIDE HEIGHTS:

LF: 8" | RF: 7 7/8" | LR: SET WEDGE | RR: 14" (TOP OF AXLE TO BOTTOM OF RR OVERRAIL)

PERCENTAGES: *WITH THE DRIVERS WEIGHT IN THE SEAT

LEFT SIDE %: 54.0 / REAR %: 56.0 / WEDGE: 60 - 100 #