

# eSTREAM™ 4K

## 2X2 STB



**eSTREAM™ 4K**  
Powered by Android TV™

### FEATURES & BENEFITS

- Delivery of superior 4KHDR, VP9, Ultra-HD content; HEVC/H.265
- Integrated Wi-Fi 2x2 802.11b/g/n/ac
- Certified with the latest version of Android TV Operating Software (Pie, 9.0)
- Access to the latest streaming apps through the Google Play Store
- Low power consumption standby

Evolution Digital continues to innovate with new solutions for pay-TV operators. Introducing eSTREAM™ 4K, powered by Android TV™. Now operators have a choice for providing a stunning, graphic-rich interactive viewing experience for their customers. eSTREAM 4K is designed to deliver superior 4K Ultra-HD resolution with four times greater image resolution than standard 1080P HD images. The streaming box also provides simplified whole-home video distribution through its integrated 802.11b/g/n/ac Wi-Fi client with 2x2 antenna configuration.

eSTREAM 4K is a bandwidth-saver by utilizing HEVC/H.265 and VP9. With its sleek and innovative design, eSTREAM 4K uses the latest technology to reduce power consumption while increasing processing capability.

Evolution Digital's eSTREAM 4K features a simplified user experience with version 9.0 "Pie" of Android TV, providing access to all popular streaming apps through the Google Play Store.

### EVOLUTION DIGITAL

7347 S Revere Pkwy, Bldg A  
Centennial, CO 80112

800.315.2253

[evolutiondigital.com](http://evolutiondigital.com)

# eSTREAM 4K 2x2 STB Specifications

| HARDWARE PLATFORM |                |
|-------------------|----------------|
| Chipset           | Amlogic S905X2 |
| RAM               | 2GB DDR3       |
| Flash             | eMMC 8GB       |

| NETWORK   |   |
|-----------|---|
| Wi-Fi     | 802.11 b/g/n/ac 2.4G/5G MIMO 2T2R Wi-Fi |
| Bluetooth | Bluetooth 5.0                           |
| SOC       | Broadcom AP6398SR3                      |

| VIDEO             |   |
|-------------------|---|
| Video Decoding    | VP9 Profile-2 up to 4Kx2K@60fps<br>H.265 HEVC MP-10@L5.1 up to 4Kx-2K@60fps<br>AVS2-P2 Profile up to 4Kx2K@60fps<br>H.264 AVC HP@L5.1 up to 4Kx2K@30fps<br>H.264 MVC up to 1080P@60fps<br>MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496)<br>WMV/VC-1 SP/MP/AP up to 1080P@60fps<br>AVS-P16(AVS+) /AVS-P2 JiZhun Profile up to 1080P@60fps<br>MPEG-2 MP/HL up to 1080P@60fps (ISO-13818)<br>MPEG-1 MP/HL up to 1080P@60fps (ISO-11172)<br>HDR; Dolby Vision, HDR10, HLG |
| Video File Format | Supports *.mkv,*.wmv,*.mpg, *.mpeg, *.dat, *.avi, *.mov, *.iso, *.mp4, *.rm and *.jpg file formats  |
| Video Output      | HDMI 2.1, HDCP2.2   |
| Aspect Ratio      | Auto, Full screen   |
| Video Resolution  | 4K@60fps 1080p/i 720p 4Kx2K@75 max resolution output  |

| AUDIO          |  |
|----------------|--|
| Audio Decoding | Supports MP3, AAC, WMA, RM, FLAC, Ogg and programmable with 7.1/5.1 down-mixing Dolby Digital/Digital Plus,DTS,WMA,WMA Pro,WMV |
| Audio mode     | Mono/Stereo/Left/Right   |

| POWER             |              |
|-------------------|--------------|
| DC Input Range    | 5V/2.0A      |
| Power Consumption | Maximum 10 W |

| INTERFACE |  |
|-----------|--|
| Interface | HDMI 2.1, IR, LED Indicator, 1-USB 2.0, 1-USB 3.0, 1-Micro SD, 1-AV Port, 1-Ethernet 10/100, DC IN, Optical S/PDIF |

| ACCESSORIES   |                           |
|---------------|---------------------------|
| RCU           | 1 PCS Bluetooth RCU       |
| User's Manual | English                   |
| DC Adaptor    | 1 PCS DC 12V/1.5A Adaptor |

| PHYSICAL FEATURES     |            |
|-----------------------|------------|
| Operating Temperature | 0°C–40°C   |
| Storage Temperature   | -10°C–65°C |
| Size (WxDxH) in mm    | 115x115x30 |

| REMOTE                                 |  |
|--|--|
| Bluetooth Enabled                      |  |
| Supports Google Assistant Voice Search |  |
| Standard Remote                        |  |

All values are typical unless noted otherwise. Specifications are subject to change without notification.