



VIEW YOUR WORLD IN HD

Stay connected to what matters most with real-time high definition security recording. Convenient one cable installation provides power to IP cameras and carries HD video to the recorder. Free FLIR Cloud™ smartphone, tablet and computer apps (PC & Mac) keep you connected to what matters most.



FLIR Cloud™



16 Channels 3TB HDD 4MP Super HD

FEATURES:

- Real-time recording with cameras up to 4MP SUPER HD @ up to 30/25fps per channel
- 16 built in PoE (Power over Ethernet) ports providing video and power on a single Ethernet cable
- Automatically detects compatible IP cameras in the network ¹
- 24/7 security-grade hard drive ²
- H.264 video compression ²
- Expandable high capacity storage up to 12TB (max 2×6TB HDD)
- Mirror hard drive recording—secure your recordings by backing up footage to an internal hard drive at the same time as recording to the primary hard drive ³
- Pentaplex operation—view, record, playback, backup & remotely control the system simultaneously
- Simultaneous playback and live view on the same screen ⁴
- Selectable area digital zoom in live view and playback
- Dynamic click-and-drag camera channel assignment
- Flip and mirror camera view settings
- Convenient front panel button controls
- Accurate time stamps with NTP & daylight savings time
- Instant USB backup of live video from selected camera
- 2 video outputs (HDMI & VGA) to connect multiple monitors
- HDMI cable included for simple connection to HD TVs
- Keep up to date with automatic firmware upgrades ⁵
- 3-step remote view with FLIR Cloud™ ⁶
- PC and Mac compatible ⁷
- Free iOS and Android compatible apps with live viewing, playback, video recording, and snap shot ⁷
- Dedicated iPad app with multi-channel live viewing and playback ⁷
- Push notifications of motion events
- Instant email alerts with snap shot attachment
- Dual streaming to conserve bandwidth
- Continuous, scheduled and motion recording



SYSTEM

Operating System	Linux (embedded)
Pentaplex	Simultaneous View, Record, Playback, Backup & Remote Monitoring
Number of Channels	16 ch

Inputs/Outputs

Video IN	16 PoE Video Input
Video OUT	No
VGA OUT	Yes
HDMI	Yes
Audio IN	1 Line IN (RCA) for service only
Audio OUT	1 Line OUT (RCA) for service only
USB Port	1 at the back, 1 at the front
Alarm IN	4 Alarm IN
Alarm OUT	2 Alarm OUT
Video Output Resolution	1920x1080, 1280x1024, 1280x720, 1024x768
PTZ control	Lorex IP PTZ cameras only

Display

Display Split	1, 4, 9, 16
Live Display Speed	480 fps NTSC, 400 fps PAL
OSD	Camera Title, Time, Camera Lock, Motion Detection, Recording Status
System Navigation	USB mouse, IR remote control, front panel buttons
Motion Area Setting	Adjustable grid (22x18)
Sensitivity Levels	100
Firmware Upgrade	Automatic over the Internet & via USB device and Network
User Authority	By user group
Time Synchronization	Auto time sync by NTP server

RECORDING

Video Compression	H.264 / MJPEG
Resolution	SUPER HD 4MP (2688x1520) / 3MP (2048x1536) / 1080p (1920x1080) / 720p (1280x720)
Record Rate	NTSC: 480fps @ up to 4MP SUPER HD PAL: 400fps @ up to 4MP SUPER HD
Recording Resolution Setting	Per camera for different resolutions
Recording Quality Control	6 levels
Recording Schedule channel	By hour, by day, by recording mode, by motion, by channel
Pre Recording	Max. 4 Secs
Post Recording	Max. 5 Minutes
Reliability	Watch-Dog, auto-recovery after power failure
Covert Video	Yes

PLAYBACK

Playback Channel	1/4/9/16
Playback Speed	Variable Max 16x
Playback Players	Backup Player
Search	By time & event
Log Search	Up to 1,000 lines for motion detected, configuration changes, connects/disconnects and video loss
Audio Play	Yes (audio camera required)

STORAGE & ARCHIVE

Storage	Up to 2 HDD's (SATA)
Maximum Capacity	Up to 2x6TB (12TB total)
Backup Media	USB Flash Drive & HDD
Backup File Format	H.264

CONNECTIVITY

Cloud Connection	FLIR Cloud™
Supported Operating Systems	Windows™ Mac OS X
Remote Software	Client Software (PC/Mac)
Email Notification	Text with snapshot
Instant Smart Phone & Tablet Support †	iPad®, iPhone®, Android™
DDNS	Free Lorex DDNS
System Configuration	Full setup configuration over network
Ports	Programmable by User
Network Protocol	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter
Network Interface	10/100/1000 Mbps, RJ-45
Network Bit Rate	320Mbps total, 48~8192kbps per camera

GENERAL

Power Consumption	Approx. 30W (no HDD included)
Supply Voltage	100VAC-240VAC, 50/60Hz
Total PoE Power Output (across all channels)	130W (Max 25W per Camera)
Unit Dimensions (W x D x H)	14.7 x 12.9 x 2.1" / 375 x 327 x 53mm
Unit Weight	5.5lbs / 2.5kg
Operating Temperature	14° ~ 131° F / -10° ~ 55° C
Humidity	10 ~ 90% RH

RECORDING RESOLUTION (PIXELS) & MAXIMUM SPEED (FPS - FRAMES PER SECOND)

		720p	1080p	3MP	SUPER HD 4MP
		1280x720	1920x1080	2048x1536	2688x1520
16ch	Total	480	480	480	480
	Per channel	30	30	30	30

NVR Inputs & Outputs



Dimensions:



Product Information:

MODEL	CONFIGURATION	PACKAGE	W x D x H Inches & millimeters	WEIGHT	CUBE	UPC Code
LNR4163S	16 ch HD NVR with 3TB HDD	Brown Box	18.5 x 6.9 x 17.9" / 470 x 175 x 455mm	10.5lbs / 4.8kg	1.3cbf / 0.04cbm	6-95529-00635-2
Includes	HD NVR with Pre-Installed HDD, HDMI Cable, Remote Control, Power Adapter, Mouse, Ethernet Cable, Quick Start Guides.					

Disclaimers:

- Compatible with Lorex HD IP cameras only. For a list of compatible cameras, please visit lorextechnology.com/support
- Recording time may vary based on recording resolution & quality, lighting conditions and movement in the scene.
- Mirror recording requires a second hard drive (not included) to be installed in the NVR. Mirrored hard drive must be as large or larger than the primary hard drive to backup all recordings. Backup begins from when the mirrored hard drive is installed and configured.
- Instant playback feature available on one camera at a time during live view (when in quad or multiple live camera viewing mode).
- The NVR firmware and software must be upgraded to the latest version to use the FLIR Cloud™ service. When the system is connected to the Internet, it will automatically alert you if there is a firmware upgrade available.
- Requires a high speed internet connection and a router (not included). A minimum upload speed of 3Mbps is required for the best video performance. Up to 3 devices may connect to the system at the same time.
- For the latest list of supported apps and devices, please visit www.lorextechnology.com/support

Lorex Corporation, a division of FLIR Commercial Systems Inc.

250 Royal Crest Court
Markham, Ontario,
Canada L3R 3S1

7055 Troy Hill Drive
Elkridge, Maryland
21075 USA

www.lorextechnology.com

© 2016 Lorex Corporation

As our product is subject to continuous improvement, Lorex Corporation & subsidiaries reserve the right to modify product design, specifications & prices without notice and without incurring any obligation. E&OE.