

LED Flushmount Fixture

FEATURES ///

- Durable white polymer diffuser
- Brushed stainless steel accent design
- Mercury-free construction
- Suitable for Damp Location use
- Easy and secure installation
- TRIAC Dimmable



PRODUCT SPECIFICATIONS ///

Body Color/Finish		
Beam Angle	120°	120°
Optical Distribution		
Lumen Output	1000 LM	1000 LM
Luminous Efficacy	56 LM/W	56 LM/W
Input Power	18 W	18 W
Input Voltage	120 Vac	120 Vac
Power Factor	0.99	0.99
THD	<0.2	<0.2
Color Temp (CCT)	3000 K	3000 K
Color Rend (CRI)	84	84
Lifetime Rating	50000 hours	50000 hours
Warranty	3 Years	3 Years
Dimmability	Triac dimmable	Triac dimmable
Operating Temp	-4 to 104 (°F)	-4 to 104 (°F)
Environment	Damp Location	Damp Location
Certification(s)		
Energy Star		Energy Star
Weight	2.4 LBS	2.4 LBS
Dimensions	13.5" (D) x 6.0" (H)	13.5" (D) x 6.0" (H)
Safety Cert	UL	UL

ORDERING INFORMATION ///

EFF-18301



CONTACT

Etrenzik LED
 (866) 267-7047 office • (678) 807-1900 Fax
 Info@etrenzik.com

169 Creamer Drive
 Alpharetta, GA 30004
 www.etrenzikLED.com / www.etrenzik.com