



NIJ 06 LEVEL II - UG062XG

NIJ PERFORMANCE DATA & TECHNICAL SUMMARY

THREAT LEVEL

II

**NIJ
0101.06
CERTIFIED**



Country of Certification: USA
Ballistic Standard: NIJ 0101.06
NIJ Model: UG062XG
Threat Level: II
Areal Density: 0.96 lb/ft²
Thickness: 0.24"
Composition: Kevlar® Comfort XLT™ / Goldflex® Hybrid
Stitching: 1"x1" Diamond Quilt in Woven Fabric, Shoulder Box and Waist Tack
Ballistic Package: 70 denier Ripstop Cover
 Nylon Urethane Backed
 Heat Sealed Seams
 Patented Internal Desiccant
Ply Count: 28
NIJ 0101.06 Size Range: C1 to C5

BALLISTIC PERFORMANCE AT CERTIFICATION

9mm New V50	1768 fps.	.357 Mag New V50	1669 fps.
9mm Conditioned V50	1737 fps.	.357 Mag Conditioned V50	1684 fps.
9mm BFS	32.5 mm	.357 Mag BFS	36.7 mm
9mm New RPI	1841.7	.357 Mag New RPI	1738.5
9mm Conditioned RPI	1809.4	.357 Mag Conditioned RPI	1754.2

SPECIAL THREAT TESTED: 9MM 127GR SXT AND 357 SIG 125GR GDHP

OPTIONAL EXTERNAL CARRIERS



Extra Concealable Carrier (CC)



Tactical Outer Carrier (TOC)



Tactical Response Carrier (TRC)



Uniform Shirt Carrier (USC)



Clean Front Carrier (CFC)



Quilted Outer Carrier (QOC)

PO Box 280 | 1 Sentry Drive | Dover, TN 37058
TOLL FREE (866) 920-5940 | FAX (866) 920-5941

www.gharmorsystems.com



READY IS THE ONLY OPTION.