



NIJ 06 LEVEL IIIA - UG3AKXP

NIJ PERFORMANCE DATA & TECHNICAL SUMMARY

**THREAT
LEVEL
IIIA**

**NIJ
0101.06
CERTIFIED**



Country of Certification:	USA
Ballistic Standard:	NIJ 0101.06
NIJ Model:	UG3AKXP
Threat Level:	IIIA
Areal Density:	1.26 lb/ft ²
Thinness:	0.28"
Composition:	Kevlar® Comfort XLT™ / Kevlar® XP™ Hybrid
Stitching:	1"x1" Diamond Quilt in Woven Fabric, Shoulder Box and Waist Tack
Ballistic Package:	200 denier Ripstop Cover Nylon Urethane Backed Heat Sealed Seams Patented Internal Desiccant
Ply Count:	25
NIJ 0101.06 Size Range:	C1 to C5

BALLISTIC PERFORMANCE AT CERTIFICATION

.357 Sig New V50	1914 fps.	.44 Mag New V50	1725 fps.
.357 Sig Conditioned V50	1890 fps.	.44 Mag Conditioned V50	1743 fps.
.357 Sig BFS	27.0 mm	.44 Mag BFS	36.4 mm
.357 Sig New RPI	1519.0	.44 Mag New RPI	1369.0
.357 Sig Conditioned RPI	1500.0	.44 Mag Conditioned RPI	1383.3

SPECIAL THREAT TESTED: 9MM 127GR SXT AND 357 SIG 125GR GDHP

OPTIONAL EXTERNAL CARRIERS



Extra
Concealable
Carrier
(CC)



Tactical
Outer
Carrier
(TOC)



Tactical
Response
Carrier
(TRC)



Uniform
Shirt Carrier
(USC)



Clean Front
Carrier
(CFC)



Quilted Outer
Carrier
(QOC)

PO Box 280 | 1 Sentry Drive | Dover, TN 37058
TOLL FREE (866) 920-5940 | FAX (866) 920-5941

www.gharmorsystems.com



READY IS THE ONLY OPTION.