

**VL-CR series**

**LED Emergency Remote Heads**

CSA, cUL, cETL, or equal

Project Reference: \_\_\_\_\_ Fixture Type: \_\_\_ Cat. No.: \_\_\_\_\_ Voltage: \_\_\_\_\_ Options: \_\_\_\_\_



3.6 - 15VDC

VL-CR-7030A



VL-CR-7030B

- Injection-molded thermoplastic ABS housing
- UL-94V-0 flame rating, fire-retardant
- Wall and ceiling mounting
- Bright SMD LED head/s
- IP Class: IP20
- Insulation: II, Range: 80m<sup>2</sup>
- Operating Temperature: 0°C - 40°C



VL-CR-7012  
120/277VAC



VL-CR-7033C  
120/347VAC

- With internal battery backup
- Backup time: >90minutes
- Nickel Cadmium Battery 3.6V 1000mAh
- Test switch and charge indicator light
- Overcharge & Over-discharge protection
- Conversion time: <0.2second
- IP Class: IP20
- Bright SMD LEDs 2x1.2W
- Operating Temperature: 0°C - 40°C

**ORDERING INFORMATION**

Product Code	Input	LED Watts	
VL-CR-7030A	3.6 - 15VDC	1x 1W	remote battery pack supplied by others
VL-CR-7030B	3.6 - 15VDC	2x 1W	remote battery pack supplied by others
VL-CR-7033C	120/347VAC	2x 1.2W	internal battery backup > 90 minutes
VL-CR-7012	120/277VAC	2x 1.2W	internal battery backup > 90 minutes