

WP-COM series
Compact LED Wall Packs

CSA, cUL, cETL, or equal

Project Reference: _____ Fixture Type: _____ Cat. No: _____ Voltage: _____ Options: _____



WP-COM-25W & 35W
Clear tempered glass lens
Cast aluminum housing
7.3" x 7.2" x 3.6"



WP-COM-30W (standard with photocell)
Clear or milky polycarbonate lens
Plastic housing
11.0" x 6.8" x 5.4"

- High performance and durability at an affordable price
- IP65, suitable for wet locations
- Suitable for -30°C to 40°C ambient temperatures
- Rugged and durable construction to withstand demanding locations
- Black finish
- 110-277V or 347V, 0-10V dimmable

ORDERING INFORMATION

| Product Code | Wattage | Lumens | Lens | CCT | CRI |
|-----------------------|---------|----------|------------------------------|-------|-----|
| WP-COM-25W-4K-UNV | 25W | 2,500 lm | Clear tempered glass | 4000K | 80 |
| WP-COM-35W-4K-UNV | 35W | 3,500 lm | Clear tempered glass | 4000K | 80 |
| WP-COM-30W-4K-UNV-__* | 30W | 3,000 lm | Clear or milky polycarbonate | 4000K | 80 |

* Use "CL" for clear lens or "ML" for milky lens (WP-COM-30W only)

ACCESSORIES / OPTIONS

| Product Code | Description |
|--------------|-------------------------------------------------------------|
| 5K | 5000K option: replace "5K" in product code above with "4K" |
| 347 | 347V option: replace "UNV" in product code above with "347" |