

SlimBay Elite

Linear LED High Bay

CSA, cUL, cETL, or equal

Project Reference: _____ Fixture Type: _____ Cat. No.: _____ Voltage: _____ Options: _____



Standard with V-hook, 3.4 ft. chain & 6 ft. cord



Optional Pendant Mount

- Over 130 lumens per watt, DLC Premium qualified *
- Rated life: L70 over 100,000 hours at 40° C
- Rugged and durable construction with die formed 24 gauge cold-rolled steel body
- White baked acrylic paint finish
- High light transmission acrylic lens, clear for maximum efficiency or frosted for visual comfort
- Field replaceable Seoul LED engine and Espen driver
- 120-277V (UNV) or 347V also available, 0-10V dimmable

ORDERING INFORMATION

Product Code	Wattage	Lumens	Lens	Dimensions	CCT	CRI
SBE2-110-FL-5000K-UNV	110W	14,410 lm	Frosted	12.6" x 23.8" x 3.6"	5000K	> 80
SBE2-162-FL-5000K-UNV	162W	21,222 lm	Frosted	17.3" x 23.8" x 3.6"	5000K	> 80
SBE4-223-FL-5000K-UNV	223W	29,213 lm	Frosted	12.6" x 45.9" x 3.6"	5000K	> 80
SBE4-321-FL-5000K-UNV	321W	41,920 lm	Frosted	17.3" x 45.9" x 3.6"	5000K	> 80
SBE4-420-FL-5000K-UNV	420W	55,020 lm	Frosted	22.0" x 45.9" x 3.9"	5000K	> 80

ACCESSORIES / OPTIONS

Product Code	Description
4000K	4000K option: replace "5000K" in product code above with "4000K" (lumens decrease about 1%)
347	347V option: replace "UNV" in product code above with "347"
CL	Clear Lens option: replace "FL" in product code above with "CL" (lumens increase about 3%)
WG	Wire Guard: add suffix "WG" to the end of product code above
SBE-PMK	Pendant Mount Kit, order as separate item
SBE-3M	3m / 9.8 ft. adjustable cable hanging kit, order as separate item
SBE-OSR	Occupancy Sensor, order as separate item, 3 step dimming: 100%, 10 to 50%, off, with daylight sensor

* All configurations except 420W in 347V are currently DLC Premium qualified, consult with factory for DLC product codes.