

VLWP series
LED Wall Packs

CSA, cUL, cETL, or equal

Project Reference: _____ Fixture Type: _____ Cat. No.: _____ Voltage: _____ Options: _____





Standard bronze finish and glass refractor



Optional wire-guard



Optional reflector cover



- High performance and durability at an affordable price
- 120+ lumens per watt, all models are DLC qualified *
- High quality shatterproof glass refractor, won't yellow and can be cleaned
- IP65 rated for wet locations, suitable for ambient temperatures from -30°C to 40°C
- Heavy duty die-cast aluminum housing, with integral secondary heat sink to maximize performance
- Polyester powder coat finish, corrosion proof, stabilized to withstand climate changes, no cracking or peeling
- 100-277V or 347V, 0-10V dimmable, optional photocell is available

ORDERING INFORMATION

Product Code	Voltage	Wattage	Lumens	Lens	CCT	CRI
VLWP040-5000K-UNV	100-277V	40W	4,800 lm	Glass	5000K	72
VLWP-060-5000K-UNV	100-277V	57W	7,200 lm	Glass	5000K	72
VLWP-040-5000K-347	347V	42W	5,200 lm	Glass	5000K	72
VLWP-060-5000K-347	347V	64W	7,900 lm	Glass	5000K	72

ACCESSORIES / OPTIONS

Product Code	Description
4000K	4000K option: replace "5000K" in product code above with "4000K"
VLWP-PC	Photocell, order as separate item
VWP-WGA	Wire guard, order as separate item
VWP-RCA	Reflector cover, order as separate item

* Consult factory for current DLC product codes.