

Included parts:

- 1ea. Decora magnetic mount
- 1ea. Rubber Face Material
- 1ea. Black tablet adapter
- 1ea. 3M™ VHB double sided tape
- 1ea. Alcohol Cleaning Pad
- 2ea. Drywall Anchors
- 2ea. #2 Philips head screws

*****NOTE: Make sure your hands are clean and free of oils prior to installing this product.**

Installation instructions for mirror, granite, and other hard flat surfaces

1. Use the included alcohol wipes to clean the metal plate on the rear of the mount, the back of your tablet, and the surface to where the mount will be attached.
2. Remove one side of the protective layer from the 3M™ double sided tape and apply it to the metal plate on the rear of the mount, between the posts.
3. Remove the other side of the protective layer.
4. Using a level to make sure the mount plate is straight, press the it onto the surface you cleaned earlier. **The plate CANNOT be moved after it is pressed it into place**, so be very careful.
5. Apply the rubber face. **Take your time with this step! The rubber CANNOT be moved or relocated once it is applied.**
 - a. Peel back one small corner of the protective layer from the rubber.
 - b. Carefully line up the rubber with a short and long edge in the countersunk area on the face, then stick the corner in place.
 - c. Once placement is determined, remove the rest of the protective layer, and carefully position and apply the rubber.
6. To apply the tablet adapter: peel off the protective backing, carefully centering it on the rear of the touch panel and press it
7. Wait a MINIMUM of 20 minutes before attaching the touch panel to the mount for the first time.

Installation instructions for drywall

1. Using a sharp pointed object and the supplied Mounting Template (printed on the other side of this card), mark the anchor locations on your wall. It is best to use a level to assure it is straight.
2. With a Phillips screwdriver, twist the drywall anchors into the drywall until they are flush with the surface. There is no need to pre-drill the locations.
3. Carefully screw the magnetic plate into the anchors until the screws are tight and flush with the surface. Be sure to not over tighten and bend the plate.
4. Follow steps 5-7 above.

Installation instructions retrofit rings and plastic boxes

1. Carefully screw the magnetic plate onto the retrofit ring or electrical box using the supplied #6 screws. Be sure not to over-tighten and bend the plate.
2. Follow steps 5-7 above.

For detailed instructions and warranty information:

www.IntuitiveUSA.com

602-759-9559

Make certain that your tablet is centered on the mount before letting go. Intuitive™ is not liable for damaged or dropped devices.