

HORNET W85 DEF TROUBLESHOOTING

FIRST TIME INSTALL

•Reference **Image 1.**

- Suction 90° hose barb.
- Dispense line - 3/4 hose barb end of meter.
- Plug to 110V outlet/20 amp breaker.

TROUBLESHOOTING IF PUMP IS NOT WORKING PROPERLY

•No pump suction

- 1) To make sure pump is sucking, remove suction hose from 90° hose barb from below pump. Turn pump ON and place hand on barb to feel for suction.
- 2) Check Micro Matic down tube for any cracks.
- 3) Confirm Micro Matic coupler is engaged by pushing down.
- 4) The suction clamps might be loose. Make sure all clamps are securely fastened.
- 5) The suction and dispense hoses might have been reversed during pump installation. Ensure both hoses were installed correctly.

•Pump does not power on

*Most common cause of this problem is the pump ran dry. See below for solutions:

•Touch metal housing underneath pump. If it's extremely hot:

- 1) Unplug pump from outlet or wall.
- 2) Allow to cool down to outside temperature.
- 3) Flip switch to OFF.
- 4) Once pump reaches outside temperature, flip switch twice (2 times ON, 2 times OFF).
- 5) Plug back in and pump should start.

•Auto nozzle does not kick off

- 1) Check for Diesel Exhaust Fluid (DEF) crystallization. If crystallization is evident, soak nozzle in hot water for 15 minutes.

Image 1.

