

Section 1. Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

| | |
|--------------|-----------|
| Product Form | Mixture |
| Trade Name | ACRYL-PEN |
| Product Code | AP |

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use Industrial. For professional use only.

1.2.2 Uses Advised Against

No additional information available

1.3 Details of the supplier of the safety data sheet**Manufacturer**

NOX-CRETE MANUFACTURING INC
1444 SOUTH 20TH STREET
OMAHA, NE 68108
Tel: 402-341-2080
Fax: 402-341-9752
E-Mail: corporate@nox-crete.com
Web Site: www.nox-crete.com

1.4 Emergency telephone number

Emergency Number Chemtrec (800) 424-9300
Chemtrec Outside of U.S. 703-527-3887

Section 2. Hazards identification**2.1 Classification of the substance or mixture**

| | |
|---------------------------|------|
| Flam Liq. 3 | H226 |
| Asp. Tox. 1 | H304 |
| Acute Tox. 4 (dermal) | H312 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2 | H319 |
| Acute Tox. 4 (inhalation) | H332 |
| resp. irrit. STOT SE 3 | H335 |
| STOT SE 3 drowsiness | H336 |
| Carc. 2 | H351 |
| STOT RE 2 | H373 |

Full text of H phrases see section 16

Adverse physiochemical, human health and environmental effects

No additional information available

2.2 Label elements

Hazard pictograms



| | | |
|---------------------------------|--|-------------|
| Signal word | Danger | |
| Hazard statements | H226 - Flammable liquid and vapor H304 - May be fatal if swallowed and enters airways H312 - Harmful in contact with skin H315 - Causes skin irritation H319 - Causes serious eye irritation H332 - Harmful if inhaled H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness H351 - Suspected of causing cancer H373 - May cause damage to ears and CNS through prolonged or repeated exposure | Flam Liq. 3 |
| Precautionary statements | | |
| Prevention: | P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood P210 - Keep away from heat/sparks/open flames/hot surfaces-No smoking P233 - Keep container tightly closed P240 - Ground/bond container and receiving equipment P241 - Use explosion-proof electrical/ventilating/light/equipment P242 - Use only non-sparking tools P243 - Take precautionary measures against static discharge P260 - Do not breathe dust/fume/gas/mist/vapors/spray P264 - Wash exposed area's thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area P280 - Wear protective gloves/protective clothing/eye protection/face protection | |
| Response: | P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician P303+P361+P353 - IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 -IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing P308+P313 - IF exposed or concerned: Get medical advice/attention P331 - Do NOT induce vomiting P337+P313 - If eye irritation persists: Get medical advice/attention P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for extinction | |
| Storage: | P403+P405+P235+P233 - Store locked up in a cool well ventilated place. Keep container tightly closed. | |
| Disposal: | P501 - Dispose of contents/container in accordance with local/regional/national/international regulations. | |

2.3 Other hazards

Full text of R, H and EUH phrases: see section 16

Section 3. Composition / information on ingredients

3.1 Substances

Not applicable

3.2 Mixture

| Name | Product identifier | % |
|-----------------------------------|--------------------|--------------|
| Xylene | 1330-20-7 | < 60.0 |
| Aromatic Solvent | Trade Secret | Trade Secret |
| Ethylbenzene | 100-41-4 | < 19.0 |
| Propylene Glycol Monomethyl Ether | 108-65-6 | Trade Secret |
| Alkyl Alkoxy Silane | Trade Secret | Trade Secret |

Pursuant to 29CFR 1910.1200(i) the specific chemical identity (and / or) concentration may be withheld as Trade Secret, while all health and safety properties and effects are included in the SDS.

Section 4. First aid measures

4.1 Description of first aid measures

First-aid measures general

Get medical advice/attention if you feel unwell. Never give anything by mouth to an unconscious person.

First-aid measures after inhalation

If the individual experiences nausea, dizziness, has difficulty In breathing seek a healthcare professional immediately. In all cases of doubt, or when symptoms persist, seek medical advice. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a Poison Center or doctor/physician.

First-aid measures after skin contact

If skin irritation persists, seek medical attention. Remove or take off immediately all contaminated clothing. Rinse skin with water or shower. Wash off immediately with soap and plenty of water.

First-aid measure after eye contact

When contact lenses are worn, remove if possible. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes while holding eyelids apart. Get medical attention immediately.

First-aid measures after ingestion

Rinse mouth. DO NOT induce vomiting. Get medical attention immediately.

4.2 Most important symptoms and effects, acute and delayed

Symptoms/injuries after inhalation

May cause irritation to the respiratory tract. Overexposure to vapors may result in headache, nausea, drowsiness or dizziness.

Symptoms/injuries after skin contact

May cause skin irritation or burning sensation

Symptoms/injuries after eye contact

May cause eye irritation or injury

Symptoms/injuries after ingestion

May cause severe irritation or burns to the mucous membrane of the mouth, throat, esophagus and stomach

4.3 Indication of any immediate medical attention and special treatment needed

No additional information available

Section 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Dry chemical, foam, carbon dioxide

Unsuitable extinguishing media

Do not use heavy water stream

5.2 Special hazards arising from the substance or mixture

Reactivity

Thermal decomposition products may cause a health hazard.

5.3 Advice for firefighters

Firefighting instructions

Flammable Liquid! This material releases vapors when heated above ambient temperatures. Vapors can cause a flash fire. Use water spray or fog to cool exposed containers.

Protective equipment for firefighters

Firefighters should always wear self-contained breathing apparatus (SCBA) and full protective gear when fighting any chemical fire.

Other information

On heating or burning harmful gasses/vapors may be released. This product may cause the floor to become slippery.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

General measures

Extremely Flammable. Eliminate any ignition sources. Dike or impound spilled material. Use Non-sparking tools. All equipment must be grounded. Take proper precautions to ensure your own health and safety before attempting spill control or cleanup.

6.11 Protective Equipment

Equip cleanup crew with proper protective equipment.

6.2 Environmental precautions

Prevent entry to sewers and public waters.

Notify authorities if liquid enters sewers or public waters.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

Soak up spills with inert solids, such as clay or diatomaceous earth. Collect into vapor tight containers and dispose of properly.

Section 7. Handling and storage

7.1 Precautions for safe handling

Protective measures

Wash hands and other exposed areas with soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in work areas to prevent formation of vapor. When not in use keep containers tightly closed. Avoid breathing vapor or mist.

Hygiene measures

Wash contaminated clothing before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Store in accordance with local regulations. Store in original container in a cool well ventilated place away from heat, sparks and open flame.. Keep containers tightly closed until ready for use.

Incompatible materials

Strong oxidizing agents

Storage temperature

Store in a cool dry environment away from sources of ignition.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

| Ingredient name | Occupational exposure limits ACGIH TLV (United States) |
|-----------------------------------|---|
| Xylene | TWA: 100 ppm 8 hours |
| Aromatic Solvent | TWA: 100 ppm 8 hours |
| Ethylbenzene | TWA: 100 ppm 8 hours |
| Propylene Glycol Monomethyl Ether | TWA: 100 ppm 8 hours |
| Alkyl Alkoxy Silane | Not established |

8.2 Exposure controls

Appropriate engineering controls

Use with adequate ventilation to keep product vapor concentrations

| | |
|--------------------------------|---|
| Eye and face protection | below specified TLV Chemical goggles and/or face shields are required to prevent potential eye contact, irritation or injury. |
| Skin protection | Wear chemical resistant gloves and appropriate protective clothing and boots as required to prevent skin contact. Wash exposed skin frequently with soap and water. Soiled clothing should be laundered before reuse. |
| Respiratory protection | General room ventilation is normally adequate. Avoid breathing the product mist or vapors. The use of an appropriate respirator is recommended whenever the airborne concentrations exceed the TLV. |

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|--------------------------------------|
| Appearance | Clear liquid |
| Odor | Strong Aromatic Odor |
| Odor Threshold | No data available |
| PH | No data available |
| Melting point | No data available |
| Freezing point | No data available |
| Boiling point | > 150 C (>300 F) |
| Flash point | 27 C 80 F PMCC |
| Relative evaporation rate (butyl acetate=1) | No data available |
| Flammability (solid, gas) | Flammable liquid and vapor |
| Upper/lower explosive limits | No data available |
| Vapor pressure | No data available |
| Vapor density | No data available |
| Relative density (Specific gravity) | 0.97 Kg per Liter 8.1 Lbs per Gallon |
| Solubility | Water: Negligible |
| Partition coefficient n-octanol/water | No data available |
| Auto-ignition temperature | Not applicable |
| Viscosity | No data available |
| VOC content | Less than 600 g/l |

Section 10. Stability and reactivity

| | |
|---|--|
| <u>10.1 Reactivity</u> | No additional information available |
| <u>10.2 Chemical stability</u> | Stable under normal conditions |
| <u>10.3 Possibility of hazardous reactions</u> | Hazardous polymerization will not occur. |
| <u>10.4 Conditions to avoid</u> | Extreme high or low temperatures. |
| <u>10.5 Incompatible materials</u> | Strong acids and oxidizers |
| <u>10.6 Hazardous decomposition products</u> | carbon monoxide, carbon dioxide, various hydrocarbon derivatives |

Section 11. Toxicology information

11.1 Information on toxicological effects

| | |
|--|---|
| Acute toxicity | No adverse effects expected under intended use. |
| Irritation/Corrosion | May cause skin irritation |
| Skin | May causes serious eye irritation and damage. |
| Eyes | May cause respiratory irritation |
| Respiration or skin sensitization | No data available |
| Germ cell mutagenicity | |
| Carcinogenicity | IARC |

| | |
|--------------|----|
| Xylene | 3 |
| Ethylbenzene | 2B |

2B - Limited evidence in humans and less than sufficient evidence in animals.

3 - Inadequate in humans and inadequate or limited in animals.

| | |
|---------------------------------------|--|
| Reproductive toxicity | No data available |
| Specific target organ toxicity | |
| Single exposure | No data available |
| Repeated exposure | No data available |
| Aspiration hazard | May be fatal if swallowed and enters airways |

Section 12. Ecological information

| | |
|---|-------------------------------------|
| 12.1 Ecotoxicity | Not established |
| 12.2 Persistence and degradability | Not established |
| 12.3 Bioaccumulative potential | Not established |
| 12.4 Mobility in soil | No additional information available |
| 12.5 Other adverse effects | Avoid release to the environment |

SECTION 13. Disposal Considerations

| | |
|-------------------------------------|--|
| 13.1 Waste treatment methods | The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all applicable local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. |
|-------------------------------------|--|

SECTION 14. Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

| | |
|--|-------------------------------------|
| 14.1 UN number | UN1263 |
| 14.2 UN proper shipping name | Paint Related Material |
| 14.3 Transport hazard class(es) | 3 |
| 14.4 Packing group | III |
| 14.5 Environmental hazards | No additional information available |
| 14.6 Special precautions for user | |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | No additional information available |
| 14.8 Transport in bulk according to CFR 49 173.15 | Not applicable |

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.2 USA Regulations

| | |
|--------------------|---|
| Section 313 | Contains the following ingredients at or above the reporting level requirements of Section 313. This information must be included in all SDS's copied or distributed for this material. |
|--------------------|---|

| CHEMICAL | CAS # | MAX WEIGHT % |
|--------------|-----------|--------------|
| Xylene | 1330-20-7 | 38.0 |
| Ethylbenzene | 100-41-4 | 8.0 |



chemical solutions
to concrete problems

ACRYL-PEN

Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), *Hazardous Products Regulation* (HPR) (WHMIS 2015)

Trimethylbenzene

95-63-6

2.2

**TSCA
Proposition 65**

All ingredients are listed or exempted
This product contains one or more chemicals known to the State of California to cause cancer and/or reproductive toxicity.

15.1.3 Canada Regulations

This SDS has been prepared according to the hazard criteria of the *Hazardous Products Regulation* (HPR) (WHMIS 2015) and the SDS contains all of the information required by the HPR.

DSL

All ingredients are listed or exempted

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

Section 16. Other information

| | |
|------------------------|------------------------------|
| Date of issue | 11-10-2015 |
| Version | 2.1 |
| Number | 102 |
| Date of previous issue | 6-1-2015 |
| Preparer | Nox-Crete Manufacturing Inc. |

Reference Documentation

The information contained herein is based on data available to us and is believed to be correct. Since this information may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and Buyer may rely thereon only at Buyers risk. We have made no effort to censor or to conceal deleterious aspects of this product. Further since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the health and/or safety precautions we have suggested will be adequate for all individuals and/or situations involving its handling or use. Likewise, we make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state or local laws. It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Disclaimer

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assumes the risk of this use thereof. (NOX-CRETE MANUFACTURING INC)

Full text of R, H and EUH phrases

| | |
|---------------------------|------|
| Flam Liq. 3 | H226 |
| Asp. Tox. 1 | H304 |
| Acute Tox. 4 (dermal) | H312 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2 | H319 |
| Acute Tox. 4 (inhalation) | H332 |
| resp. irrit. STOT SE 3 | H335 |
| STOT SE 3 drowsiness | H336 |
| Carc. 2 | H351 |
| STOT RE 2 | H373 |

