

HXLIGHTING

X8™ Type B Touch-Safe Tubes



Safe, high-efficiency replacements for fluorescent tubes in:

- Offices
- Showrooms
- Warehouses and storage facilities
- Retail locations
- Schools
- Refrigerated storage areas
- Outdoor/vapor-proof fixtures
- Anywhere T8 fluorescent tubes are used



(Fixture not included)

Features

- Exceptional light quality – 300 degree dispersion – Low glare
- Earth-friendly design contains no mercury or lead.
- Built-in ASIC Safety Switch eliminates shock risk during installation
- Instant on at full brightness – no warm-up time
- Dual-end design works with shunted sockets - No ballast required
- Superior quality **High-Efficiency HX Driver™** - 120-277 volt
- Frosted glass tube will not sag or yellow - no pixelation
- Excellent heat dissipation
- **EcoHX PLUS™**, Outdoor, Cool and Natural color tones
- Extreme Performance – 50,000+ User Hours – 36 Month Warranty
- Optional **HX-Guard™** safety coating
- Complete retrofit kits and fixtures available



WARRANTY



CRI (Ra)



LIFETIME HOURS



INSTANT ON

Product Code	Length	Wattage	Description	Color Tone	CRI	Lumens	Case Qty.
LX84LV17EXP	4ft.	17W	LED/X8/4FT/120-277V/17W/EcoHX PLUS	EcoHX PLUS	90+	2400	36
LX84LV17O	4ft.	17W	LED/X8/4FT/120-277V/17W/EcoHXO	Outdoor	85+	2200	36
LX84LV17C	4ft.	17W	LED/X8/4FT/120-277V/17W/EcoHXC	Cool	85+	2200	36
LX84LV17N	4ft.	17W	LED/X8/4FT/120-277V/17W/EcoHXN	Natural	85+	2200	36
LX83LV12O	3ft.	12W	LED/X8/3FT/120-277V/12W/EcoHXO	Outdoor	85+	1600	36
LX83LV12C	3ft.	12W	LED/X8/3FT/120-277V/12W/EcoHXC	Cool	85+	1600	36
LX83LV12N	3ft.	12W	LED/X8/3FT/120-277V/12W/EcoHXN	Natural	85+	1600	36
LX82LV9EXP	2ft.	9W	LED/X8/2FT/120-277V/9W/EcoHX PLUS	EcoHX PLUS	90+	1300	36
LX82LV9O	2ft.	9W	LED/X8/2FT/120-277V/9W/EcoHXO	Outdoor	85+	1200	36
LX82LV9C	2ft.	9W	LED/X8/2FT/120-277V/9W/EcoHXC	Cool	85+	1200	36
LX82LV9N	2ft.	9W	LED/X8/2FT/120-277V/9W/EcoHXN	Natural	85+	1200	36

