

UV Tracer

A light viscosity, lithium soap thickened, polyolester grease
Intended for electrical contact and small precision bearing applications.

Ford: WSS-M1C255-A1

Lubricant Properties		Typical value	Test Method
Recommended Service Range (°C)		-54 to 150	
Thickener		Lithium Soap	
Base oil	Type	Ester	
	Kinematic viscosity	100°C	4.1 cSt
		40°C	18.5 cSt
	Viscosity Index		125
	Flash point	°C	256
	Pouring point	°C	-67
Typical Properties of the Grease		Typical value	Test Method
Color, Appearance		Tan, Smooth	
Penetration (1/10 mm)	NLGI Grade	2	ASTM D-217
	Unworked	267	ASTM D-217
	Worked	60X	281
Density		25°C	0.91 g/cm ³
Oil Separation	24 hour(s)	100°C	4.6
			FTM 791, Method 321.2
Evaporation	24 hour(s)	100°C	0.3 %
			NYE CTM

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1503)

Distributed by Newgate Simms Limited

Broughton Mills Road, Bretton, Chester, CH4 0BY, United Kingdom
+44(0)1244 660771 www.newgatesimms.com info@newgatesimms.com