

UV Tracer, Copper Deactivator

A Polyurea thickened, medium viscosity, synthetic hydrocarbon grease for lubrication and protection of electrical contacts. Benefits include high temperature performance and insertion force reduction.

Lubricant Properties		Typical value	Test Method
Recommended Service Range (°C)		-40 to 175	
Thickener		Urea	
Base oil	Type	PAO/ Alkylated Naphthalene	
	Kinematic viscosity	100°C	22 cSt
		40°C	193 cSt
		-40°C	331176 cSt
	Viscosity Index		138
	Flash point	°C	286.0000
	Pouring point	°C	-42
Typical Properties of the Grease		Typical value	Test Method
Color, Appearance		Tan, Smooth	
Penetration (1/10 mm)	Unworked		257
	Worked	60X	277
		10K	321
	NLGI Grade	2	
Density	25°C	0.911 g/cm ³	NYE CTM
Oil Separation	24 hour(s)	100°C	2.6
Evaporation	24 hour(s)	100°C	0.3 %

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1510)

Distributed by Newgate Simms Limited

Broughton Mills Road, Bretton, Chester, CH4 0BY, United Kingdom
+44(0)1244 660771 www.newgatesimms.com info@newgatesimms.com