



Magnum 5W-20 Synthetic Blend Motor Oil API-SN, ILSAC GF-5

Attributes

- Formulated with high-viscosity index type II paraffinic and synthetic base stocks
- Superior anti-shear properties
- Unique detergent additive prevents sludge or carbon deposits in extreme heat or pressure conditions
- Enhances engine performance
- Extends oil life, ease cold-starts
- Eliminates viscosity breakdown
- Exceeds API SN, ILSAC GF-5

Typical Properties

SAE J300 Viscosity	5W-20
Appearance	Amber, Bright, Free & Clear
Viscosity cSt @ 40°C	46.95
Viscosity cSt @ 100°C	8.2
Pour Point, °C	-42
Flash Point, °C	210
Viscosity Index	150

Exceeds Specification Requirements

API – SN	API - SM	API - SL
ILSAC GF-5	ILSAC GF-4	ILSAC GF-3
GM 6094M	Ford WSS-M2C-945-A	Chrysler MS-6395

Product Codes

Bulk	ATO-001	NA
275 Gal Tote	ATO-001-T	SKU 703980627754
55 Gal Drum	ATO-001-D	SKU 703980627709
5 Gal Pail	ATO-001-P	SKU 703980627655
3/5 Quart Case	ATO-001-FG	SKU 782290771920
12/1 Quart Case	ATO-001-Q	SKU 670875447417

Distributed by Ataram Oil Company
1331 Regal Row, Dallas, TX 75241
(214)785-3360

