



High Mileage 5W-30 Synthetic Blend Motor Oil API-SN, ILSAC GF-5

Attributes

- Specially formulated for use in gasoline engines with over 75,000 miles
- Fortified with conditioners, seal-swell agents, enhanced corrosion and oxidation protection, and enhanced shear stability specifically to protect older engines
- Enhances engine performance
- Extends oil life
- Eases cold-starts
- Eliminates viscosity breakdown
- Exceeds API SN, ILSAC GF-5

Typical Properties

SAE J300 Viscosity	5W-30
Appearance	Amber, Bright, Free & Clear
Viscosity cSt @ 40°C	64.25
Viscosity cSt @ 100°C	11.0
Pour Point, °C	-42
Flash Point, °C	210
Viscosity Index	165

Exceeds Specification Requirements

API - SN	API - SM	API - SL
ILSAC GF-5	ILSAC GF-4	ILSAC GF-3
GM 6094M	Ford WSS-M2C-946-A	Chrysler MS-6395

Product Codes

Bulk	ATO-002-HM	NA
275 Gal Tote	ATO-002-HM-T	SKU 782290771784
55 Gal Drum	ATO-002-HM-D	SKU 782290771838
5 Gal Pail	ATO-002-HM-P	SKU 782290771883
3/5 Quart Case	ATO-002-HM-FQ	SKU 703980627488
12/1 Quart Case	ATO-002-HM-Q	SKU 782290771982

Distributed by Ataram Oil Company
1331 Regal Row, Dallas, TX 75241
(214)785-3360

