



Magnum 5W-30 Synthetic Blend Motor Oil API-SN, ILSAC GF-5

Attributes

- Formulated with high-viscosity index type II paraffinic and synthetic base stocks
- Superior anti-shear properties
- Unique detergent additive prevents sludge or carbon deposits in extreme heat or pressure conditions
- Enhances engine performance
- Extends oil life, ease cold-starts
- Eliminates viscosity breakdown
- Exceeds API SN, ILSAC GF-5

Typical Properties

SAE J300 Viscosity	5W-30
Appearance	Amber, Bright, Free & Clear
Viscosity cSt @ 40°C	64.25
Viscosity cSt @ 100°C	11.0
Pour Point, °C	-42
Flash Point, °C	210
Viscosity Index	165

Exceeds Specification Requirements

API – SN	API - SM	API - SL
ILSAC GF-5	ILSAC GF-4	ILSAC GF-3
GM 6094M	Ford WSS-M2C-946-A	Chrysler MS-6395

Product Codes

Bulk	ATO-002	NA
275 Gal Tote	ATO-002-T	SKU 703980627761
55 Gal Drum	ATO-002-D	SKU 703980627716
5 Gal Pail	ATO-002-P	SKU 703980627662
3/5 Quart Case	ATO-002-FQ	SKU 782290771937
12/1 Quart Case	ATO-002-Q	SKU 670875447400

Distributed by Ataram Oil Company
1331 Regal Row, Dallas, TX 75241
(214)785-3360

