



High Mileage 10W-30 Synthetic Blend Motor Oil API-SN, ILSAC GF-5

Attributes

- Specially formulated for use in gasoline engines with over 75,000 miles
- Fortified with conditioners, seal-swell agents, enhanced corrosion and oxidation protection, and enhanced shear stability specifically to protect older engines
- Enhances engine performance
- Extends oil life
- Eases cold-starts
- Eliminates viscosity breakdown
- Exceeds API SN, ILSAC GF-5

Typical Properties

SAE J300 Viscosity	10W-30
Appearance	Amber, Bright, Free & Clear
Viscosity cSt @ 40°C	69.55
Viscosity cSt @ 100°C	11.0
Pour Point, °C	-37
Flash Point, °C	215
Viscosity Index	150

Exceeds Specification Requirements

API – SN	API - SM	API - SL
ILSAC GF-5	ILSAC GF-4	ILSAC GF-3
GM 6094M	Chrysler MS-6395	

Product Codes

Bulk	ATO-003-HM	NA
275 Gal Tote	ATO-003-HM-T	SKU 782290771791
55 Gal Drum	ATO-003-HM-D	SKU 782290771845
5 Gal Pail	ATO-003-HM-P	SKU 782290771890
3/5 Quart Case	ATO-003-HM-FQ	SKU 703980627495
12/1 Quart Case	ATO-003-HM-Q	SKU 782290771999

Distributed by Ataram Oil Company
1331 Regal Row, Dallas, TX 75241
(214)785-3360



Distributed by Ataram Oil Company
1331 Regal Row, Dallas, TX 75241
(214)785-3360

