



Magnum 10W-30 Synthetic Blend Motor Oil API-SN, ILSAC GF-5

Attributes

- Formulated with high-viscosity index type II paraffinic and synthetic base stocks
- Superior anti-shear properties
- Unique detergent additive prevents sludge or carbon deposits in extreme heat or pressure conditions
- Enhances engine performance
- Extends oil life, ease cold-starts
- Eliminates viscosity breakdown
- Exceeds API SN, ILSAC GF-5

Typical Properties

SAE J300 Viscosity	10W-30
Appearance	Amber, Bright, Free & Clear
Viscosity cSt @ 40°C	69.55
Viscosity cSt @ 100°C	11.0
Pour Point, °C	-37
Flash Point, °C	215
Viscosity Index	150

Exceeds Specification Requirements

API – SN	API - SM	API - SL
ILSAC GF-5	ILSAC GF-4	ILSAC GF-3
GM 6094M	Chrysler MS-6395	

Product Codes

Bulk	ATO-003	NA
275 Gal Tote	ATO-003-T	SKU 703980627778
55 Gal Drum	ATO-003-D	SKU 703980627723
5 Gal Pail	ATO-003-P	SKU 703980627679
3/5 Quart Case	ATO-003-FQ	SKU 782290771944
12/1 Quart Case	ATO-003-Q	SKU 670875447495

Distributed by Ataram Oil Company
1331 Regal Row, Dallas, TX 75241
(214)785-3360

