



High Mileage 10W-40 Synthetic Blend Motor Oil API-SN

Attributes

- Specially formulated for use in gasoline engines with over 75,000 miles
- Fortified with conditioners, seal-swell agents, enhanced corrosion and oxidation protection, and enhanced shear stability specifically to protect older engines
- Enhances engine performance
- Extends oil life
- Eases cold-starts
- Eliminates viscosity breakdown
- Exceeds API SN

Typical Properties

SAE J300 Viscosity	10W-40
Appearance	Amber, Bright, Free & Clear
Viscosity cSt @ 40°C	99.3
Viscosity cSt @ 100°C	14.4
Pour Point, °C	-37
Flash Point, °C	215
Viscosity Index	150

Exceeds Specification Requirements

API – SN API - SM API – SL API-SJ

Product Codes

Bulk	ATO-004-HM	NA
275 Gal Tote	ATO-004-HM-T	SKU 782290771807
55 Gal Drum	ATO-004-HM-D	SKU 782290771852
5 Gal Pail	ATO-004-HM-P	SKU 782290771906
4/1 Gal Case	ATO-004-HM-G	SKU 782290771951
12/1 Quart Case	ATO-004-HM-Q	SKU 782290772002

Distributed by Ataram Oil Company
1331 Regal Row, Dallas, TX 75241
(214)785-3360

