



High Mileage 20W-50 Synthetic Blend Motor Oil API-SN

Attributes

- Specially formulated for use in gasoline engines with over 75,000 miles
- Fortified with conditioners, seal-swell agents, enhanced corrosion and oxidation protection, and enhanced shear stability specifically to protect older engines
- Enhances engine performance
- Extends oil life
- Eases cold-starts
- Eliminates viscosity breakdown
- Exceeds API SN

Typical Properties

SAE J300 Viscosity	20W-50
Appearance	Amber, Bright, Free & Clear
Viscosity cSt @ 40°C	154.75
Viscosity cSt @ 100°C	18.5
Pour Point, °C	-25
Flash Point, °C	220
Viscosity Index	135

Exceeds Specification Requirements

API – SN

Product Codes

Bulk	ATO-005-HM	NA
275 Gal Tote	ATO-005-HM-T	SKU 782290771814
55 Gal Drum	ATO-005-HM-D	SKU 782290771869
5 Gal Pail	ATO-005-HM-P	SKU 782290771913
4/1 Gal Case	ATO-005-HM-G	SKU 782290771968
12/1 Quart Case	ATO-005-HM-Q	SKU 782290772019

Distributed by Ataram Oil Company
1331 Regal Row, Dallas, TX 75241
(214)785-3360

