



ROAD WARRIOR 15W-40
SYNTHETIC BLEND HEAVY-DUTY MOTOR OIL
 API - CK-4/SN

Attributes

- High performance multi-grade parasynthetic lubricant
- Designed for use in high speed, four-stroke diesel engines
- Designed for use in carbureted, fuel injected, turbocharged and supercharged gasoline engines
- Designed for superior protection against wear, corrosion, oxidation and varnish
- Unique detergent additive prevents sludge or carbon deposits in extreme heat or pressure conditions
- Formulated with high viscosity-index Type II paraffinic base stocks
- High-viscosity index synthetic Type II paraffinic base stocks
- Superior anti-shear properties
- Extends oil life
- Eliminates viscosity breakdown.
- Enhances engine performance
- Eases cold-starts

Typical Properties

SAE J300 VISCOSITY GRADE	15W-40
Appearance	Amber, Bright, Free & Clear
Viscosity cSt @ 40°C	103.4
Viscosity cSt @ 100°C	14.5
Pour Point, °C	-30
Flash Point, °C	220
Viscosity Index	145

Exceeds Specification Requirements

API CK-4/SN, CJ-4, CI-4 Plus, CH-4, CF-4

Product Codes

BULK	ATO-101	NA
275 Gal Tote	ATO-101-T	SKU 703980627860
55 Gal Drum	ATO-101-D	SKU 703980627839
5 Gal Pail	ATO-101-P	SKU 703980627808
3/2 Gal Case	ATO-10-TG	SKU 703980627624

Distributed by Ataram Oil Company ,1331 Regal Row, Dallas, TX 75241
 (214)785-3360

