



LIMITLESS FULL SYNTHETIC MOTOR OIL

10W-30

API - SN, ILSAC GF-5

Attributes

- Full Synthetic (100% Synthetic) Basestocks
- Exceeds Specification Requirements of API – SN, ILSAC GF-5
- Protection Against Sludge and Carbon Deposits
- Superior Protection Against Wear
- Superior Protection Against Corrosion and Oxidation
- Extends Drain Intervals
- Improves Fuel Economy
- Excellent Cold-Flow Properties
- Superior Anti-Shear Properties

Technical Data

SAE Viscosity Grade	10W-30
API Service Class	SN
Viscosity cSt @ 40°C	63.75
Viscosity cSt @ 100°C	10.5
Viscosity Index (VI)	155
Flash Point °C	220
Pour Point °C	-37
Cold Crank, cP@°C	<7000@25

Exceeds Specification Requirements:

API - SN	API - SM	API - SL
ILSAC - GF-5	ILSAC - GF-4	ILSAC GF-3
GM 6094M	Chrysler MS-6395	

Product Codes

Bulk	ATO-204	NA
275 Gal Tote	ATO-204-T	SKU 782290771081
55 Gal Drum	ATO-204-D	SKU 782290771036
5 Gal Pail	ATO-204-P	SKU 703980627921
3/5 Quart Case	ATO-204-FQ	SKU 703980627532
12/1 Quart Case	ATO-204-Q	SKU 782290771760

Distributed by Ataram Oil Company
 1331 Regal Row, Dallas, TX 75241
 (214)785-3360 Sales@ataramoil.com

