EURO 5W-40

FULL SYNTHETIC MOTOR OIL

API – SN, ACEA C3

Attributes

-Full Synthetic (100% Synthetic) Basestocks
-Premium Additive Protection
-Protection Against Sludge and Carbon Deposits
-Suitable for use in applications which require ACEA C3
-Superior Protection Against Corrosion and Oxidation
-Exceeds Performance Requirements of API SN
-Extends Drain Intervals
-Improves Fuel Economy
-Superior Anti-Shear Properties
-Excellent Cold-Flow Properties
-Superior Protection Against Wear

Typical Specifications

SAE Viscosity Grade	*5W-40*
API Service Class	SN
Viscosity cSt @ 40°C	84.5
Viscosity cSt @ 100°C	14.2
Viscosity Index (VI)	175
Flash Point °C	215
Pour Point °C	-42
Cold Crank, cP@°C	<6600@30

Suitable For Use:

API - SN API - SM API - SL API – SJ
ACEA C3-10

Product Code:

Bulk	ATO-205	NA
275 Gal Tote	ATO-205-T	SKU 782290771098
55 Gal Drum	ATO-205-D	SKU 782290771043
5 Gal Pail	ATO-205-P	SKU 703980627938
3/5 Quart Case	ATO-205-FQ	SKU 703980627549

Distributed by Ataram Oil Company
1331 Regal Row, Dallas, TX 75241
(214)785-3360 Sales@ataramoil.com