



AW HYDRAULIC OIL ISO 32

Attributes

- Formulated with high viscosity-index paraffinic base stocks and premium performance additives
- Excellent oxidation stability, corrosion protection, shear stability, and pumpability
- Designed for wide array of operating conditions and temperatures
- Comprehensive additive package includes anti-wear, anti-corrosion, anti-foaming agents as well as detergency
- Acceptable for a wide-range of applications
- Resist oxidation, rust, corrosion, foaming, varnish, and wear.

Typical Properties

TYPE	ISO 32
Appearance	Amber, Bright, Free & Clear
Viscosity cSt @ 40°C	32
Viscosity cSt @ 100°C	5.56
Pour Point, °C	-25
Flash Point, °C	215
Viscosity Index	110

Exceeds Specification Requirements

- | | |
|----------------------------------|---|
| -Dennison HF-0, HF-1, HF-2 | -Cincinnati Machine P-68, P-69, P-70 |
| -Eaton Vickers M-2950-S, I-286-S | -General Motors LS-2, LH-03, LH-04, LH-06 |
| -JCMAS HK | -US Steel 127 |

Product Codes

BULK	ATO-301	NA
275 Gal Tote	ATO-301-T	SKU 782290771173
55 Gal Drum	ATO-301-D	SKU 782290771142
5 Gal Pail	ATO-301-P	SKU 782290771111

Distributed by Ataram Oil Company, 1331 Regal Row, Dallas, TX 75241
(214)785-3360

