



AW HYDRAULIC OIL ISO 46

Attributes

- Formulated with high viscosity-index paraffinic base stocks and premium performance additives
- Excellent oxidation stability, corrosion protection, shear stability, and pumpability
- Designed for wide array of operating conditions and temperatures
- Comprehensive additive package includes anti-wear, anti-corrosion, anti-foaming agents as well as detergency
- Acceptable for a wide-range of applications
- Resist oxidation, rust, corrosion, foaming, varnish, and wear.

Typical Properties

TYPE	ISO 46
Appearance	Amber, Bright, Free & Clear
Viscosity cSt @ 40°C	46
Viscosity cSt @ 100°C	7.05
Pour Point, °C	-27
Flash Point, °C	220
Viscosity Index	110

Exceeds Specification Requirements

- Dennison HF-0, HF-1, HF-2
- Eaton Vickers M-2950-S, I-286-S
- JCMAS HK
- Cincinnati Machine P-68, P-69, P-70
- General Motors LS-2, LH-03, LH-04, LH-06
- US Steel 127

Product Codes

BULK	ATO-302	NA
275 Gal Tote	ATO-302-T	SKU 782290771395
55 Gal Drum	ATO-302-D	SKU 782290771326
5 Gal Pail	ATO-302-P	SKU 782290771258

Distributed by Ataram Oil Company, 1331 Regal Row, Dallas, TX 75241
(214)785-3360

