



SYNTHETIC GEAR OIL
SAE 75W-90
 API GL-5

Attributes

- Formulated with synthetic base oils and a premium gear additive package
- Formulated to provide improved high-temperature thermal and oxidative stability in a wide range of operating conditions
- Provide advanced protection and lubricity in extreme pressure conditions
- Highly shear stable while also resisting rust, oxidation, foaming, and varnish
- Designed to exceed the year-around, all-weather performance viscosity requirements of SAE J306 as well as the rigorous performance requirements of API GL-5
- Provided protection against the combination of thermal degradation, component wear, and oil seal deterioration

Typical Properties

SAE VISCOSITY	75W-90
Appearance	Light Yellow to Amber, Transparent Liquid, Free & Clear
Viscosity (cSt) @ 40 °C	95.9
Viscosity (cSt) @ 100 °C	15.0
Viscosity Index	165
Flash Point COC, °C	220

Exceeds Performance Requirements:

API GL-5	Mack GO-J Plus	ZFTE-ML07A
API MT-1	SAE J2360	Scania STO 1:0
MIL-L-2105D	MIL-PRF-2105E	

Product Code:

BULK	ATO-403	NA
275 Gal Tote	ATO-403-T	SKU 782290771357
55 Gal Drum	ATO-403-D	SKU 782290771289
5 Gal Pail	ATO-403-P	SKU 782290771210
12/1 Quart	ATO-403-Q	SKU 670875447448

Distributed by Ataram Oil Company ,1331 Regal Row, Dallas, TX 75241
 (214)785-3360



Distributed by Ataram Oil Company ,1331 Regal Row, Dallas, TX 75241
(214)785-3360

