



**SYNTHETIC GEAR OIL**  
**SAE 80W-140**  
 API GL-5

***Attributes***

- Formulated with high viscosity-index, paraffinic base oils and specialty performance additives
- Formulated to provide improved high-temperature thermal and oxidative stability in a wide range of operating conditions
- Provide advanced protection and lubricity in extreme pressure conditions
- Highly shear stable while also resisting rust, oxidation, foaming, and varnish
- Designed to exceed the year-around, all-weather performance viscosity requirements of SAE J306 as well as the rigorous performance requirements of API GL-5
- Provided protection against the combination of thermal degradation, component wear, and oil seal deterioration

***Typical Properties***

SAE VISCOSITY	80W-140
Appearance	Light Yellow to Amber, Transparent Liquid, Free & Clear
Viscosity (cSt) @ 40 °C	188.9
Viscosity (cSt) @ 100 °C	25
Viscosity Index	165
Flash Point COC, °C	225

***Exceeds Performance Requirements:***

API GL-5	Mack GO-J Plus	
API MT-1	SAE J2360	ZFTE-ML07A
MIL-L-2105D	MIL-PRF-2105E	Scania STO 1:0

***Product Code:***

BULK	ATO-404	NA
275 Gal Tote	ATO-404-T	SKU 782290771364
55 Gal Drum	ATO-404-D	SKU 782290771296
5 Gal Pail	ATO-404-P	SKU 782290771227

Distributed by Ataram Oil Company ,1331 Regal Row, Dallas, TX 75241  
 (214)785-3360

