



**AUTOMATIC TRANSMISSION FLUID
DEXRON III / MERCON**

Attributes

- Formulated with high viscosity-index paraffinic base stocks and premium performance additives
- Designed for excellent oxidation stability, thermal resistance, and excellent friction modification properties
- Recommended where a Dexron-III/Mercon fluid is required
- Suitable for power steering units where a Dexron III or Mercon fluid is recommended.
- Suitable for mobile hydraulic and industrial systems, and rotary air compressors under specified service requirements

Typical Properties

PARAMETER	TYPICAL
Appearance	Red, dyed
Viscosity cSt @ 40°C	36.1
Viscosity cSt @ 100°C	7.35
Viscosity Index	175
Pour Point, °C	-51
Flash Point, °C	185

Exceeds Performance Requirements

GM DEXRON®, DEXRON® II, II-E, III, III-G, III-H
Ford MERCON®, M2C-33, M2C-138-CJ, M2C-166-H or Type A
Detroit Diesel Allison C-3, C-4
Caterpillar TO-2

Product Code:

BULK	ATO-501	NA
275 Gal Tote	ATO-501-T	SKU 782290771487
55 Gal Drum	ATO-501-D	SKU 782290771449
5 Gal Pail	ATO-501-P	SKU 782290771401
12/1 Quart Case	ATO-501-Q	SKU 670875447448

Distributed by Ataram Oil Company ,1331 Regal Row, Dallas, TX 75241
(214)785-3360

