



Full Synthetic, Universal CVT Fluid

(Continuously Variable Transmission Fluid)

Attributes

- Designed to provide superior protection and performance to chain or push belt continuously variable transmissions
- Suitable for use in many CVT applications
- Exhibits outstanding shear stability (stay-in-grade viscometrics)
- Protects against metal-to-metal wear
- Provides outstanding oxidation stability coupled with excellent low temperature properties.

Typical Properties

PARAMETER	TYPICAL
Appearance	Red, dyed
Viscosity cSt @ 40°C	34.3
Viscosity cSt @ 100°C	7.2
Viscosity Index	180
Pour Point, °C	-50
Flash Point, °C	190

Suitable for Use

- Audi : TL 52180; G052 180 A2; G052 516
- Chrysler : CVTF+4
- Dodge / Jeep : NS-2; CVTF+4/MOPAR CVTF+4
- Ford : CFT23; CFT30 / Mercon C
- GM/Saturn : DEX-CVT
- Hyundai / Kia : SP-CVT-1
- Nissan : NS-1; NS-2; NS-3
- Mercedes Benz : CVT28 / MB 236.20
- Mitsubishi : DiaQueen CVTF-J1; DiaQueen CVTF-J4
- Shell : Green 1V
- Subaru : CV-30; e-CVTF
- Toyota : Fluid TC; Fluid FE
- VW : TL 52180, G 052 180 A2; G 052 516
- BMW : 83 22 0 136 376; 83 22 0 429 154 (EZL 799A)
- Daihatsu : Amix CVTF-DC; Amix CVTF-DFE; Fluid TC
- Ford : CVT WSS-M2C-933-A / XT-7QCFT
- Fujijyuuko : i-CVTF FG
- Honda : Multimatic Fluid (HMMF); HCF-2
- Lexus : Fluid TC; Fluid FE
- Mazda : CVTF 3320
- Mini Cooper : EZL 799A / ZF CVT V1
- Punch : EZL 799A
- Subaru : i-CVTF; Lineartronic CVTF; K0425Y0710
- Suzuki : CVTF 3320; TC; NS-2; CVTF Green 1; CVTF Green 2
- Volvo : CVT 4959

Product Code

BULK	ATO-504	NA
275 Gal Tote	ATO-504-T	SKU 782290771517
55 Gal Drum	ATO-504-D	SKU 782290771470
5 Gal Pail	ATO-504-P	SKU 782290771432
12/1 Quart Case	ATO-504-Q	SKU 670875447462

Distributed by Ataram Oil Company, 1331 Regal Row, Dallas, TX 75241
(214)785-3360



Distributed by Ataram Oil Company, 1331 Regal Row, Dallas, TX 75241
(214)785-3360

