



SAE 10W

HD Transmission/Drivetrain Oil Caterpillar TO-4

Attributes

- High-performance multi-purpose transmission and drivetrain fluid
- Designed for powershift transmissions, final drives, wet brakes, differentials, hydraulic, and power-steering units
- Formulated with high viscosity-index type II paraffinic base stocks and premium performance additives
- Provides maximum gear life and capacity for wet brakes and power-take-off clutches, excellent wet brake noise suppression and filterability characteristics
- Specially blended to prevent rust, corrosion, foaming and oxidation

Typical Properties

<u>TYPE</u>	<u>SAE 10W</u>
Appearance	Amber, Bright, Free & Clear
Viscosity cSt @ 40°C	42.4
Viscosity cSt @ 100°C	6.4
Pour Point, °C	-30
Flash Point, °C	200
Viscosity Index	100

Suitable For Use

- Allison C-4
- Caterpillar TO-4

Product Codes

BULK	ATO-602	NA
275 Gal Tote	ATO-602-T	SKU 782290771616
55 Gal Drum	ATO-602-D	SKU 782290771579
5 Gal Pail	ATO-602-P	SKU 782290771531

Distributed by Ataram Oil Company, 1331 Regal Row, Dallas, TX 75241
(214)785-3360

