

TECH LINE Coatings

SAFETY DATA SHEET

Section 1 – Identification

Product Identifier: CLCFL

Part Number:

Recommended Use: Premix of DS1105 minor components

Restrictions on Use:

Manufacturer / Supplier:

Tech Line Coatings, Inc

26844 ADAMS AVE.

MURRIETA, CA 92562

USA

Phone/Fax 1-865-773-0599

www.techlinecoatings.com

Keep out of reach of children.

Not recommended for use on Medical equipment.

Not recommended for use on Aviation equipment.

Emergency Phone: N.America +1-800-535-5053

Intl. +1-352-323-3500

Section 2 – Hazards Identification

Signal Word:

Danger

Symbols:



Hazard Statements:

Highly flammable liquid and vapor

Harmful if inhaled

Causes skin Irritation

Causes Serious Eye Irritation

May cause drowsiness or dizziness

GHS Classification:

Category

Flammable Liquid 2

Acute Toxicity Inhalation 3

Skin Irritation 2

Eye Damage / Irritation 3

Specific Target Organ 3

Toxicity Single Exposure

Precautionary Statements:

Keep away from heat / sparks / open flames / hot surfaces. - No Smoking. Ground / bond container and receiving equipment. Use explosion proof electrical / ventilating / lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

In case of fire use alcohol-resistant foam, dry chemical or carbon dioxide

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Wear protective gloves / protective clothing (chemical proof). Wear eye protection and face protection. Wash hands, face and any exposed skin thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat drink or smoke when using this product. Do not breath fumes / mist / vapors / spray. Use only outdoors or in a well ventilated area.

If on skin: wash with plenty of water. If skin irritation occurs get medical advice / attention. Immediately take off all contaminated clothing and wash it before reuse.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center / doctor for medical advice.

If in eyes: Rinse cautiously in water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists: get medical advice attention.

Dispose of Contents / container in accordance with regulations in your area. See section 13 for additional information.

Section 3 – Composition / Information On Ingredients

<u>Component Name</u>	<u>Common Name / Synonyms</u>	<u>CAS#</u>	<u>% of Weight</u>
Tert Butyl Acetate	TBAC	540-88-5	> 70%
n-Butyl acetate		123-86-4	> 13%

Other ingredients are not hazardous based on OSHA standard Section 29 CFR 1910.1200

Section 4 – First Aid Measures

General Advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water, and remove contaminated clothing shoes and leather goods. Consult a physician..

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Section 5 – Fire Fighting Measures

Extinguishing Media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.	Special Fire Fighting Procedures: Wear self contained breathing apparatus for fire fighting if necessary.
Unusual Fire And Explosion Hazards: Hazardous decomposition products formed under extreme fire conditions. - Carbon and other oxides. Vapors are heavier than air and may travel to a source of ignition and flash back.	Additional Information: Use water spray to cool unopened containers.

Section 6 – Accidental Release Measures

Methods for Containment and Clean Up

- Soak up with inert absorbent material.
- Keep in suitable, marked and closed containers for disposal.
- Use spark-proof tools and explosion-proof equipment.
- Remove sources of ignition.
- Warn other workers of spill.
- Wear protective equipment
 - NIOSH Approved Respirator
 - Gloves
 - Safety Glasses
- Do not allow material to be released into the environment.

Additional Information:

- See Section 7 for safe handling information.
- See Section 8 for PPE information
- See Section 13 for disposal information

Section 7 – Handling And Storage

Handling:

Do not breathe vapors or mists from spraying. Avoid contact with skin and eyes. Use with adequate ventilation to maintain exposure levels below established exposure limits. Wear personal protective equipment. If required wear an appropriate NIOSH approved respirator with paint prefilter. Use explosion-proof equipment. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures

against static discharges.

Storage:

Store in area suitable for flammable liquids. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Protect from oxidizers, inorganic acids, aldehydes, and isocyanates.

Section 8 – Exposure Controls And Personal Protection

Component	ACGIH TLV	OSHA	NIOSH REL
Tert Butyl Acetate	TWA 200 PPM	TWA 200 PPM	1,500 PPM
n-Butyl acetate	TWA 150 ppm	TWA 150 ppm STEL 200 ppm	TWA 150 ppm STEL 200 ppm

Engineering Controls:

Exhaust ventilation.
Showers
Eyewash stations
Use in a well-ventilated area.

Respiratory Protection:

Use NIOSH approved respirator if TWA/TLV limits are exceeded

Protective Gloves:

CHEMICAL RESISTANT

Eye Protection:

SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES

Other Protective Equipment:

WEAR PROTECTIVE CLOTHING, CHEMICAL RESISTANT OR OTHER PROTECTIVE OUTERWEAR AVOID CONTACT WITH SKIN OR EYES

Ventilation:

Local Exhaust: Use To Maintain Below TWA Limits

Mechanical:

Use Non-Sparking Equipment

Work / Hygienic Practices:

wash thoroughly after handling product and before eating, drinking or smoking

Section 9 – Physical And Chemical Properties

Form :	liquid
Color :	Clear
Odor :	Mixture of Solvents
Odor Threshold:	Not Established
pH :	No data available
Melting point/range :	No data available
Initial boiling point :	> 200° F.
Flash point :	> 61° F.
Evaporation Rate:	No data available on mixture
Upper/lower flammability or explosive limits:	No data available on mixture
Vapor pressure	No data available on mixture
Vapor density	> 1 - (air =1)
Relative density	No data available on mixture
Solubility(ies)	No data available on mixture
Partition coefficient: n-octanol/water	No data available on mixture
Auto-ignition temperature	No data available on mixture
Decomposition temperature	No data available on mixture
Viscosity	No data available on mixture

Section 10 – Stability And Reactivity

Stability:	STABLE
Possibility of hazardous reactions:	Hazardous Polymerization: Will not occur.
Conditions to avoid:	Avoid storage of open containers at elevated temperatures. Heat, flames and sparks, direct sunlight.
Incompatible Materials:	Oxidizing material can cause a reaction.
Hazardous Decomposition Products:	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silicon dioxide. Carbon oxides. Metal oxides. Formaldehyde.

Section 11 – Toxicological Information

Potential Health Effects

Inhalation	Harmful if inhaled. May cause respiratory tract irritation. Vapours may cause drowsiness and dizziness.
Ingestion	May be harmful if swallowed.
Skin	May be harmful if absorbed through skin. Causes skin irritation.
Eyes	Causes eye irritation.

Acute Toxicity

Tert Butyl Acetate	Oral LD50	LD50 Oral - rat - 4,100 mg/kg Remarks: Behavioral:Altered sleep time (including change in righting reflex). Behavioral:Ataxia. Lungs, Thorax, or Respiration:Dyspnea.
	Inhalation LC50	LC50 Inhalation - rat - 4 h - > 2,230 mg/m3
	Dermal LD50	LD50 Dermal - rabbit - > 2,000 mg/kg Remarks: Diarrhoea Kidney, Ureter, Bladder:Other changes.
n-Butyl acetate	Oral LD50	LD50 Oral - rat - 10,700 - 14,130 mg/kg
	Inhalation LC50	LC50 Inhalation - rat - 4 h - > 21.0 mg/l
	Dermal LD50	LD50 Dermal - rabbit - 17,600 mg/kg

Skin Corrosion/Irritation

TBAc
Skin - rabbit - Mild skin irritation
n-Butyl acetate
Skin - rabbit - Skin irritation - 24 h

Serious Eye Damage/Eye Irritation

TBAc
Eyes - rabbit - Mild eye irritation
n-Butyl acetate
Eyes - rabbit - Moderate eye irritation

Respiratory Or Skin Sensitization

No data available

Germ Cell Mutagenicity

No data available

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

This product contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

Reproductive Toxicity

No data available

Specific Target Organ Toxicity Single Exposure

n-Butyl acetate

May cause drowsiness or dizziness.

Specific Target Organ Toxicity Repeated Or Prolonged Exposure

No data available

Aspiration Hazard

No data available

Section 12 – Ecological Information

General Comments:

Do not allow material to be released into the environment without proper governmental permits

Environmental Toxicity:

Tert Butyl Acetate

Toxicity to fish

LC50 - Pimephales promelas (fathead minnow) - 296 - 362 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates

No data available

n-Butyl acetate

Toxicity to fish

LC50 - Lepomis macrochirus (Bluegill) - 100 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 72.8 - 205.0 mg/l - 24 h

Section 13 – Disposal Considerations

Waste Disposal Method:

RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? Yes

Characteristic Waste:

Ignitable: D001

TCLP: D018

State or local laws may impose additional regulatory requirements regarding disposal.

Contaminated Packaging

Dispose of as unused product.

Section 14 – Transportation Information

Hazardous for Shipping: Yes
Based on 49 CFR, IATA and IMDG:
UN Number: UN1263
UN Proper Shipping Name: Paint related material
Hazard Class: 3
Packing Group: II

Labels: Flammable Liquid

Placards: Flammable Liquid

Section 15 – Regulations

TSCA (Toxic Substances Control Act) Regulations, 40 CFR 710: All hazardous ingredients are on the TSCA Chemical Substance Inventory.

Component	%	CAS Number	SARA 313	SARA 302	New Jersey RTK List	Pennsylvania RTK List	Massachusetts RTK List	California Prop 65 list
Tert Butyl Acetate	> 70%	540-88-5	No	No	Yes	Yes	Yes	No
n-Butyl acetate	> 13%	123-86-4	No	No	Yes	Yes	Yes	No

* Please note that these were random sample analyses and content may vary from batch to batch.

SARA 311 / 312 Hazards: Flammable Hazard ,Acute Health Hazard, Chronic Health Hazard

Section 16 – Other Information

Date Prepared: 04/01/2014
Date Updated: 08/10/2017
Date Printed: 12/28/2017

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Tech Line Coatings, Inc., knowledge or obtained from sources believed by Tech Line Coatings, Inc. to be accurate but does not purport to be all inclusive, and Tech Line Coatings, Inc., does not assume any legal responsibility for use or reliance upon same. Before using any chemical, read its label, instructions and material safety data sheet.