



Section 01 - Product and company identification

Identification of the company Prairie Mud Service
738-6th St.
Estevan, Sk., S4A 1A4

Emergency Telephone Number: 306-634-3411

Trade name: **A-35X**

Material number: 100005034

Chemical family: Mixture

Primary product use: Additive

Section 02 - Hazards identification

Classification:

WHMIS controlled: yes

Class: B2
D2A
D2B



Flammable
Causes skin and eye irritation.
Harmful by inhalation, in contact with skin and if swallowed.

Health effects of exposure:

Flammable
Toxic by ingestion
Toxic by inhalation and in contact with skin.
Irritating to eyes and skin.
Xylene (o,m,p- isomers): are reported as teratogenic and reproductive effectors in rodents. The substance is toxic to blood, kidneys, the nervous system, liver. Repeated or prolonged exposure can cause cumulative effects in target organs. Inhalation of high concentrations may cause irritation of the nose and throat and signs of nervous system depression (headache, fatigue, dizziness and drowsiness).

Listed carcinogen: IARC: Yes
NTP: Yes OSHA: No

Section 03 - Composition/information on ingredients

Hazardous ingredients:

Component	CAS number	Concentration
Xylene	1330-20-7	60 - 100 %
Ethylbenzene	100-41-4	0.5 - 1.5 %

Component toxicity information:

Xylene (1330-20-7)
Acute oral toxicity: LD50 4,300 mg/kg (Rat)

Section 04 - First aid measures

After inhalation:

Move the victim to fresh air.
Give oxygen or artificial respiration if needed.
Get immediate medical advice/ attention.
Never give anything by mouth to an unconscious person.

After contact with skin:

Remove contaminated clothing and wash affected areas with soap and plenty of water for at least 15 minutes. If redness or skin irritation occurs, seek medical attention.

After contact with eyes:

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.

After ingestion:

Never give anything by mouth to an unconscious person. If swallowed, do not induce vomiting. Give large quantities of water immediately to reduce concentration. Seek medical attention immediately.

Advice to doctor / Treatment: None known.

Section 05 - Fire fighting measures

Extinguishing media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool containers/tanks with water spray.

Unusual fire and explosion hazards: Burning produces noxious and toxic fumes. Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure.

Section 06 - Accidental release measures**Steps to be taken in case of spill or leak:**

Only trained personnel should be involved in spill operations. Wear suitable protective equipment. Ensure adequate ventilation. Remove all ignition sources. Contain spill and pump into proper containers using explosion-proof equipment. Smaller spills may be recovered using an inert non-combustible absorbent material (sand, kieselguhr) and collected into suitable containers. Do not use organic absorbent material. Containers in which spilled substance has been collected must be properly labelled. Spill may be covered with appropriate foam to hinder the formation of explosive vapours. Wash spill area. Do not allow to enter sewers, storm drains, surface waters or the soil.

Section 07 - Handling and storage**Advice on safe handling:**

Keep away from heat, sparks and open flames. - Avoid breathing vapors or contact with skin, eyes, and clothing. - Use only with adequate ventilation and proper protective eyewear, face shield, gloves and clothing. Wash thoroughly after handling. Keep container closed.

Further info on storage conditions:

Keep containers tightly closed in a cool, well-ventilated place. Handle and open container with care. Keep away from sources of ignition.

Section 08 - Exposure controls /personal protection

Respiratory protection: Wear an approved respirator when exposed to vapours or to mists beyond the TLV. Use appropriate filters. Do not exceed filters limitations. TLV = Threshold Limit Value

Hand protection: Butyl Rubber, PVC or Neoprene

Eye protection: Tightly fitting safety goggles

Other protective equipment: Avoid skin contact. Wear suitable protective clothing.

Advice on system design: Local ventilation recommended - mechanical ventilation maybe used.

Section 09 - Physical and chemical properties

Form: Liquid

Color: amber

Solubility in water: insoluble

Density: 0.8950 - 0.9100 g/cm³

Section 10 - Stability and reactivity

Hazardous Polymerization: Hazardous polymerisation does not occur.

Incompatibility with (Conditions to avoid) : Keep away from heat.
Keep away from open flames, hot surfaces and sources of ignition.

Section 11 - Toxicological information

Skin irritation: irritating
The product has not been tested. The information is derived from the properties of the individual components.

Eye irritation: irritating
The product has not been tested. The information is derived from the properties of the individual components.

Sensitization: non-sensitizing
The product has not been tested. The information is derived from the properties of the individual components.

Section 12 - Ecological information

Product information:**Remarks:**

The product should not be allowed to enter drains, water courses or the soil. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Section 13 - Disposal considerations

Waste disposal information:

Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities.

Section 14 - Transport information

TDG

Proper shipping name:	Flammable liquid, n.o.s.
Class:	3
Packing group:	III
UN/ID number:	UN 1993
Primary risk:	3
Remarks:	Shipment permitted
Hazard inducer(s):	Xylene
Ethylbenzene	

IATA

Proper shipping name:	Flammable liquid, n.o.s.
Class:	3
Packing group:	III
UN/ID number:	UN 1993
Primary risk:	3
Remarks:	Shipment permitted
Hazard inducer(s):	Xylene
Ethylbenzene	

Proper shipping name:	Flammable liquid, n.o.s.
Class:	3
Packing group:	III
UN no.:	UN 1993
Primary risk:	3
Hazard inducer(s):	Xylene
Ethylbenzene	

Section 15 - Regulatory information
--

Registration status

DSL:	yes
NDSL:	no

All components of the product are listed on the DSL/Canada.

CEPA

Listed as priority substance: yes Listed astoxic substance: no

NPRI

yes

TSCA Status:

All components of this product are listed on the TSCA Inventory.

FDA:

This product is not registered with the FDA.

Section 16 - Other information

Revised: May 1, 2019

The information contained on this SDS is to the best of our knowledge an accurate summary of the data available as of the date of preparation. Prairie Mud Service is not liable for the application or use of this information in situations beyond its control or outside the normal and expected use of its product. Prairie Mud Service. assumes no responsibility for damage or injury from the use of the product described herein.