

# AIR TREATMENT

## dropout<sup>®</sup> WATER SEPARATORS

The Dropout<sup>®</sup> Auto-Drain is designed to remove all contaminants from the Dropout<sup>®</sup> units automatically. The Dropout<sup>®</sup> Compact Water Separator is unique and patent protected, designed to revolutionize the compressed air industry. Dropout<sup>®</sup> is a scientifically engineered and multi-stage Compressed Air Filter that removes 99.9999% of liquid (water & oil) and 99% solid particulates down to 1 micron.



**DROPOUT<sup>®</sup> AUTO-DRAIN**

### SPECIFICATIONS

Port Size:	1/2" BSPT
Flow Rate:	203 cfm
Max. Supply Pressure:	232 psi
Water Storage:	11.8 oz.
Operating Temperature:	32-176°F

### KEY BENEFITS

- Drains all contaminants automatically
- Maintenance free
- No main power or batteries required
- Easy to install

PART #	DESCRIPTION
PDOAD128	AUTOMATIC DRAIN

### SPECIFICATIONS

Port Size:	3/4" BSPT
Flow Rate:	35 cfm
Max. Supply Pressure:	232 psi
Water Storage:	9.5 oz.
Drain Connection:	1/2" MBSPT

### KEY BENEFITS

- Guaranteed 99.9999% liquid water removal
- ISO 12500 Certified parts 3 & 4
- Sealed for life aluminum housing
- No increase in pressure drop caused by blocked filters
- No drop in liquid water or particle removal efficiency
- Multiple impact design operates more efficiently than others

PART #	DESCRIPTION
PDO600A	3/4" BSPT, BAR, COMPACT



**DROPOUT<sup>®</sup> COMPACT WATER SEPARATOR**