

# AIR TREATMENT FILTERS, REGULATORS, & LUBRICATORS



**FILTER-REGULATOR**

PCL's Filter-Regulator units are designed to eliminate moisture and particulates from the air flow. The Filter-Regulator units come complete with a wall bracket and pressure gauge.

SPECIFICATIONS	ATC6	ATC12
Port Size:	1/4" NPT	1/2" NPT
Adjustment:	0-174 psi	0-232 psi
Max. Supply Pressure:	174 psi	232 psi
Drain Bowl Capacity:	1 oz.	1.7 oz.
Max. Temperature:	140°F	140°F

### KEY BENEFITS

Manual/semi-automatic drain

10 micron filter

Locking device

Complete with wall bracket and pressure gauge

### PART # DESCRIPTION

<b>ATC6</b>	FILTER-REGULATOR, 1/4" NPT
<b>ATC12</b>	FILTER-REGULATOR, 1/2" NPT

PCL's Filter-Regulator-Lubricator units are designed to control output air pressure, eliminate moisture and contaminants from the air flow, and to lubricate tools during use. The FRL units come complete with a wall bracket and a pressure gauge.

SPECIFICATIONS	ATCFRL6	ATCFRL12
Port Size:	1/4" NPT	1/2" NPT
Max. Supply Pressure:	174 psi	232 psi
Drain Bowl Capacity:	1.35 oz	2.4 oz
Oil Bowl Capacity:	1.01 oz	1.70 oz
Max. Temperature:	140°F	140°F
Lubrication Adjustment (1 drop):	79-758.5 gal./min.	

### KEY BENEFITS

Manual/semi-automatic drain

10 micron filter

Locking device

Complete with wall bracket and pressure gauge

### PART # DESCRIPTION

<b>ATCFRL6</b>	FILTER-REGULATOR-LUBRICATOR, 1/4" NPT
<b>ATCFRL12</b>	FILTER-REGULATOR-LUBRICATOR, 1/2" NPT



**FILTER-REGULATOR-LUBRICATOR**